

**Sprayer with pressure tank**



- » The filling is very easy and effected by means of a plastic hopper to fill in.
- » 1/4" M connection to be attached at the compressed-air supply.
- » Max. 8 bar. Equipped with a default safety valve.
- » Chemically resistant hose 10 m. Spray lance 600 mm with nozzle. Fill level indication.
- » Suitable for the use in the car wash and industry.
- » **Available from 10 pieces in other RAL colors.**

R+M Nr.	TYP	📦
106 024 500	coated steel	24 l
106 050 500 🚚	coated steel	50 l
106 100 500 🚚	coated steel	100 l

**Foamer with pressure tank**



- » The filling is very easy and effected by means of a plastic hopper to fill in.
- » 1/4" M connection to be attached at the compressed-air supply.
- » Max. 8 bar. Equipped with a default safety valve.
- » Chemically resistant hose 10 m. Foam lance 600 mm with nozzle head and 4 nozzles. Fill level indication.
- » Integrated dosing unit to realise the desired air/foam mixture. Permanent pressure exposure is required in order to achieve an uniform foam result.
- » Suitable for the use in the car wash and industry.
- » **Available from 10 pieces in other RAL colors.**

R+M Nr.	TYP	📦
106 024 550	coated steel	24 l
106 050 550 🚚	coated steel	50 l
106 100 550 🚚	coated steel	100 l

For storing and applying Group 2 liquids according to Pressure Equipment Directive 2014/68/EU, Article 13:  
Not suitable for liquids of group 1 and especially strong alkaline solution and acids.

**Accessories for sprayer and foamer**

Foam hoses	Spray hoses	Foam head	Nozzles			
Bayonet. 10 m	1/4" M. 10 m	1/2" M	Foamer. 55° 55	Foamer. 60° 25	Sprayer. 110° 04	Sprayer. 110° 045
R+M Nr. 106 901 01	R+M Nr. 106 911 01	R+M Nr. 106 906 0	R+M Nr. 609 805 59	R+M Nr. 609 802 59	R+M Nr. 609 110 04	R+M Nr. 609 110 045

Symbols TYP type 📦 volume 🚚 shipment by truck