

INTERPUMP motor pumps

Standard



Motor pump with switch and cable.
Dimensions: 455 x 320 x 258 mm.

Repair kits

01	02	03	04
Valves 6 pieces	Seal kit for 1 piston	Sleeve kits for 3 pistons	Oil seal kits for 3 pistons
05	06	07	08
Ceramic socket for 1 piston		Valve plugs. Kit with 6 plugs	O-ring for valve plugs 1 piece

Standard		Total stop	01	02	03	04	05	06	07	08					
P	U	KW	TYP	V	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.				
120	14	1,450	3.8	M14-120	400	001 200 01	001 200 03	340 123 01	340 131 01	340 127 01	340 023 01	440 401 09		340 124 01	903 847 00

INTERPUMP high pressure pumps for petrol engines

Version "C"



Repair kits

01	02	03	04
Valves 6 pieces	Seal kit for 1 piston	Sleeve kits for 3 pistons	Oil seal kits for 3 pistons
05	06	07	08
Ceramic socket for 1 piston		Valve plugs. Kit with 6 plugs	O-ring for valve plugs 1 piece

Version "CV"



"C"		"CV"	01	02	03	04	05	06	07	08				
P	U	KW	TYP	Serie	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.			
150	13	3,400	3.67	TT1513C	51	015 130 07	340 123 01	340 096 01	340 097 01	340 083 01	510 400 09		340 157 01	903 847 00
170	15	3,400	4.77	WW961C	44	009 610 06	340 123 01	340 130 01	340 088 01	340 023 01	520 400 09		340 124 01	903 847 00
170	17.4	3,400	5.51	WW962C	44	009 620 06	340 123 01	340 130 01	340 088 01	340 125 01	520 400 09		340 124 01	903 847 00
200	16	3,400	6.1	UH2016	63	020 160 17	340 123 01	340 166 01	340 160 01	340 159 01	520 400 09		340 124 01	903 847 00

Valves

- Type "H" is equipped with an automatic pressure regulator that allows to zero the pump pressure.
- Type "K" is equipped with an automatic pressure regulator that allows to zero the pressure in the entire system (pump and hose).

Shaft

- 3/4" ■ 1"

Symbols P pressure ⇐ flow U revolutions KW kilowatt TYP type V voltage