

Accessories antistatic

Vacuum tubes antistatic



R+M Nr.	M	↔	∅
264 023 01	<=10 ⁴ Ω/m electrically efferent	500 mm	45 mm



R+M Nr.	M	↔	∅
265 023 01	<=10 ⁴ Ω/m electrically efferent	500 mm	58 mm

Hose coupling antistatic



R+M Nr.	M	∠F	∅
264 052 01	10 ⁴ Ω/m	38 mm	45 mm



R+M Nr.	M	∠L	∅
265 050 01	10 ⁴ Ω/m	50 mm	58 mm

Vacuum tools antistatic



R+M Nr.	M	I	∅
264 019	10 ⁴ Ω/m	245 mm	45 mm



R+M Nr.	M	I	∅
265 019 01	10 ⁴ Ω/m	230 mm	58 mm

Vacuum hoses black antistatic

- 50 °C - + 60 °C. 10⁶ Ω/m electrically efferent

Black



R+M Nr.	TYP	DN	Outer ∅	↔
262 548 30	A	25 mm	35,5 mm	30 m
263 646 30	∠A	32 mm	40,5 mm	30 m
264 046 30	∠F	38 mm	48,0 mm	30 m
265 046 30	∠L	50 mm	61,0 mm	30 m

∠S ∠A = DN 32 . ∠F = DN 38 . ∠L = DN 50 . ∠R = DN 38 . ∠B = 35 mm . ∠G = 45 mm . ∠H = 38 mm . ∠M = 50 mm . ∠O = 58 mm



Symbols I height ↔ length ∅ diameter in mm ∅ internal diameter TYP type M material DN nominal diameter