
Surface cleaner with air recovery system and integrated gum remover, Mosmatic







- » Such as the other devices of the FL-AH series the new FL-AH-KAU is a record performance regarding quality, finish and excellent cleaning result. We do not know anybody who has not yet seen places such as railway stations, stadiums, schools and many more which are covered with hundreds of chewing gums. This development is the best solution against this appearance!
- » In order to ensure an effective removal of the gums the special nozzle is positioned behind the stainless steel cap. The surface is cleaned in a conventional way by means of the gun which is mounted at the right side. In case of removing stubborn dirt e.g. chewing gums the special nozzle is switched on by the gun mounted at the left side. The gums are cut up and totally removed by the hp jets and finally sucked in.
- » By means of four 100 mm plastic rolls the surface cleaner can be easily moved.

- » The frame as well as all mounting parts made out of stainless steel offer additional stability. Best cleaning results are achieved due to the height adjustable housing.
- » The swivel has reinforced self-lubricating stainless steel ball bearings and a dual spring based carbide seal system especially designed for higher revs. This combination guarantees a very long durability.
- » 2 spray guns ST-2605 equipped with the patented LTF technology, 2 hp nozzles 15° 03 and a special nozzle for the removal of chewing gums are included. Further nozzle sizes are available on request.
- » Suitable for 50 mm suction hose. Suction hose is excluded.
- » Max. 350 bar / 120 °C. Min. 15 l/min / 250 bar

R+M Nr.	Ø	Œ	8
108 809 61	520 mm	3/8" F	20 kg

LTF - Low Trigger Force 90 % reduced holding force and 40 % reduced trigger force against usual market guns.

Floor cleaner Mosmatic

FL-EB 200

FL-ABB 200



Stainless steel. 2 flat stream nozzles 15° 1/8" M are required. Min. 18 l/min / 150 bar. Max. 350 bar / 120 °C

viax. 350 bar / 120 °C			
R+M Nr.	Ø	Œ	E
108 780 35	200 mm	1/4" F	2.7 kg

- » Floor cleaner graffiti removing by
- » Field of application: graffiti removing, restoration of different surfaces, maintenance of buildings and exclusively designed for applications with high water pressure

means of suction system

- » Suitable for applications from the outside e.g. concrete, brick, lime stone buildings or wooden surfaces
- » Suitable for 50 mm suction hose
- » Our spray gun ST-2605 (202 605 500) equipped with the patented LTF system is recommended for effortless cleaning applications
- » The high pressure gun and nozzles Max. 275 bar / 120 °C are excluded

Stainless steel. 2 flat stream nozzles 15° 1/8" M are required. Max. 275 bar / 120 °C

- sidewalks, windows etc.
 » Our spray gun ST-2605
 - (202 605 500) equipped with the patented LTF system is recommended for effortless cleaning applications

» Floor cleaner - economy

» This multifunction floor cleaner

applications such as brick-lined

walls, boat walls, bases, stairs,

is especially designed for all

» The high pressure gun and nozzles are excluded

R+M Nr.	Ø	Œ.	8
108 780 02	200 mm	1/4" F	2.7 kg