













Cartridge filter for cleaning devices

	R+M Nr.	TYP	∅	⊙	I	dust class	manufacturer number
	268 268 710	PET / screen	275 mm	218 mm	183 mm	M	ALTO/WAP: 107400562 Protool: 626 437
	268 269 000	paper / screen	185 mm	150 mm	201 mm	M	Rowenta ZR-70
	268 269 100	paper / screen	190 mm	145 mm	166 mm	M	Thomas: 787 421
	268 269 300	paper	122 mm	79 mm	113 mm	M	Top-Craft (NT 0506)
	268 280 210	paper	length	↔	I	M	Festool: 452 065 Kärcher: 6.904-068
	268 280 220	PES	215 mm	115 mm	58 mm	M	Kärcher: 6.904-123
	268 228 200	paper	length	↔	I	L	Kärcher: 6.414-498
	268 228 300	paper	length	↔	I	L	Kärcher: 6.904-206
	268 228 310	paper	length	↔	I	M	Kärcher: 6.904-367
	268 228 330	PES	239 mm	140 mm	56 mm	M	Kärcher: 6.904-360
	268 228 400	paper	length	↔	I	M	Festool: 456 077
	268 228 600	paper	length	↔	I	M	Kärcher: 6.904-283
	268 228 620	PES	300 mm	140 mm	68 mm	M	Kärcher: 6.904-284
	268 228 700	paper	length	↔	I	L	Kärcher: 5.731-020
	268 289 400	paper	length	↔	I	L	ALTO/WAP: 61605

dust class

L

max. 1 %

transmittance

keeps 99.995 % back from:
 » dusts with max. concentration of > 1 mg/m³
 keeps 99.9 % back from:
 » dusts with max. concentration of > 0.1 mg/m³
 » wood dusts (up to 1200 W/50 l)

endangerings

dust class

H

transmittance

max. 0.01 %

endangerings

keeps 99.995 % back from:
 » dusts with max. concentration
 » cancer-causing dusts
 » dusts with pathogenic germs

M

max. 0.10 %