

Vacuum hoses oil-resistant

Hose profile-coiled made out of polyester-elastomer.

Features: An internally smooth profile hose made out of full plastic having a very low flow resistance and a good reset force (after pressing it together or bending it over) with excellent flexibility, high resistance to oil and fuel.

Range of applications: industrial vacuum cleaner, chemical plant engineering, conveyor and extraction systems, car exhaust systems, hot air.

Temperature range: - 60 °C - + 120 °C (temporary up to + 150 °C)



R+M Nr.	TYP	DN	Outer ∅	↔
263 644 *	A	36 mm	44.7 mm	1 - 20 m
263 644 20	A	36 mm	44.7 mm	20 m
265 044 *	L	50 mm	61.0 mm	1 - 25 m
265 044 25	L	50 mm	61.0 mm	25 m

Suction swivel arm

easywash365+

New for self-service vacuum cleaning

- » entirely made out of stainless steel
- » solid construction
- » suspension

The vertical **easywash365 +** suction swivel arm for self-service!

This cost-effective solution is ideal for single suction places.

In this case, the arm does not necessarily have to be integrated into the cabinet technology, but can be easily mounted on a wall. Perfect if space might be limited, because due to its construction this boom needs little space and bending over offers a lot of mobility.

The built-in spring prevents kinking of the suction hose and allows a barrier-free handling with optional freedom of mobility.

The vertical **easywash365 +** suction swivel arm is completely made out of stainless steel and is supplied including a mounting bracket.

Height 2,320 mm.

Tube height 1,500 mm.

Internal tube diameter of 65 mm.

Weight 10.1 kg



R+M Nr.
109 001 500

* per metre

Ⓢ A = DN 32 . Ⓣ F = DN 38 . Ⓛ L = DN 50 . Ⓡ R = DN 38 . Ⓟ B = 35 mm . Ⓠ G = 45 mm . Ⓡ H = 38 mm . Ⓡ M = 50 mm . Ⓡ O = 58 mm

