

Saugerzubehör antistatisch

Saugrohre antistatisch



R+M Nr.	\overline{M}	\overline{L}	$\overline{\varnothing}$
264 023 01	10 ⁴ Ω/m elektrisch ableitend	500 mm	45 mm



R+M Nr.	\overline{M}	\overline{L}	$\overline{\varnothing}$
265 023 01	10 ⁴ Ω/m elektrisch ableitend	500 mm	58 mm

Anschlussmuffen antistatisch



R+M Nr.	\overline{M}	\overline{F}	\overline{G}
264 052 01	10 ⁴ Ω/m	38 mm	45 mm



R+M Nr.	\overline{M}	\overline{L}	$\overline{\varnothing}$
265 050 01	10 ⁴ Ω/m	50 mm	58 mm

Saugerdüsen antistatisch



R+M Nr.	\overline{M}	\overline{I}	$\overline{\varnothing}$
264 019	10 ⁴ Ω/m	245 mm	45 mm



R+M Nr.	\overline{M}	\overline{I}	$\overline{\varnothing}$
265 019 01	10 ⁴ Ω/m	230 mm	58 mm

Saugerschläuche schwarz antistatisch

- 50 °C - + 60 °C. 10⁶ Ω/m elektrisch ableitend

Schwarz



R+M Nr.	TYP	DN	Außen $\overline{\varnothing}$	\overline{L}
262 548 30	A	25 mm	35,5 mm	30 m
263 646 30	\overline{A}	32 mm	40,5 mm	30 m
264 046 30	\overline{F}	38 mm	48,0 mm	30 m
265 046 30	\overline{L}	50 mm	61,0 mm	30 m

\overline{S} \overline{A} = DN 32 . \overline{F} = DN 38 . \overline{L} = DN 50 . \overline{R} = DN 38 . \overline{B} = 35 mm . \overline{G} = 45 mm . \overline{H} = 38 mm . \overline{M} = 50 mm . $\overline{\varnothing}$ = 58 mm



Symbole \overline{I} Höhe \overline{L} Länge $\overline{\varnothing}$ Durchmesser in mm $\overline{\varnothing}$ Innendurchmesser TYP Typ \overline{M} Material DN Nennweite