

Vacuum motors

Applies to all wet and dry motors

- » 2-ball bearings
- » Double insulation
- » Insulation class "B"



1 stage. 230 V / 50 Hz.
Cable type 3 enclosed

R+M Nr.	TYP	W	I	TI	Ø
262 101	universal	1,000	144	45	144



2 stage. 230 V / 50 Hz.
Cable type 1 enclosed

R+M Nr.	TYP	W	I	TI	Ø
262 080 102	361	800	163	72	144
262 100 102	7568	1,000	170	72	144
262 120 102	7778-5	1,200	178	72	144
262 120 302	7363-12	1,200	163	72	144
262 120 702	586-2	1,200	170	67	144

With thermal safety device

R+M Nr.	TYP	W	I	TI	Ø
262 120 202 *	7778-4	1,200	178	72	144
262 140 102 *	7788	1,400	176	72	144



2 stage. 230 V / 50 Hz.
Cable type 2 enclosed

R+M Nr.	TYP	W	I	TI	Ø
262 120 502	A210	1,200	181	67	144



1 stage. 230 V / 50 Hz.
Cable type 2 enclosed

R+M Nr.	TYP	W	I	TI	Ø
262 110 101	061200219	1,100	133	49	148



2 stage. 230 V / 50 Hz.
Cable type 2 enclosed

R+M Nr.	TYP	W	I	TI	Ø
262 100 202	BDS 10302	1,000	167	70	144
262 120 602	BDS 12382	1,200	176	70	144



2 stage. 230 V / 50 Hz.
Cable type 3 enclosed

R+M Nr.	TYP	W	I	TI	Ø
262 120	069203004	1,200	176	67	144



2 stage. 230 V / 50 Hz.
Cable pre-installed

R+M Nr.	TYP	W	I	TI	Ø
262 120 802	universal	1,200	170	66	144



1 stage. 230 V / 50 Hz.
Cable pre-installed

R+M Nr.	TYP	W	I	TI	Ø
262 110 001	061200043	1,100	136	50	144



2 stage. 24 V.
Cable pre-installed

R+M Nr.	TYP	W	I	TI	Ø
262 050 230	069103006	500	171	68	144



2 stage. 230 V / 50 Hz.
Cable pre-installed

R+M Nr.	TYP	W	I	TI	Ø
262 110 102	116 110-01	1,100	170	69	145



2 stage. 230 V / 50 Hz. Cable pre-installed.
TYP Universal

R+M Nr.	VPE	W	I	TI	Ø
262 120 902	1	1,200	172	66	148
262 120 902 006	6	1,200	172	66	148