

Vacuum motors



1 stage. 230 V / 50 Hz.
Without cable, (Cable type 1 optional)

| R+M Nr. | TYP | W | h | Ti | ∅ |
|-------------|-----------|-------|-----|----|-----|
| 262 120 703 | 063700003 | 1,200 | 136 | 46 | 143 |
| 262 120 701 | 064200001 | 1,200 | 131 | 45 | 127 |



1 stage. 230 V / 50 Hz. Cable enclosed.
With thermo switch

| R+M Nr. | TYP | W | h | Ti | ∅ |
|-------------|--------|-----|-----|----|-----|
| 262 080 101 | 203-19 | 800 | 110 | 30 | 110 |



1 stage. 230 V / 50 Hz.
Without cable, (Cable type 1 optional)

| R+M Nr. | TYP | W | h | Ti | ∅ |
|-------------|-----------|-------|-----|----|-----|
| 262 100 001 | 063200074 | 1,050 | 122 | 45 | 132 |



1 stage. 230 V / 50 Hz.
Without cable, (Cable type 1 optional)

| R+M Nr. | TYP | W | h | Ti | ∅ |
|-------------|-----------|-------|-----|----|-----|
| 262 120 801 | 063200085 | 1,200 | 128 | 51 | 132 |

Further vacuum motors are available on request.

Vacuum motor cable



Cable lug 6.3 : cable lug 4.8.
Cable 500 mm.
Cable type 1

| R+M Nr. |
|-------------|
| 262 000 001 |



Fork 3.5 : open.
Cable 300 mm.
Cable type 2

| R+M Nr. |
|-------------|
| 262 000 002 |



Wire end ferrule 2.8 : open.
Cable 300 mm.
Cable type 3

| R+M Nr. |
|-------------|
| 262 000 003 |

Carbon brushes



| R+M Nr. | suitable for R+M Nr. |
|-------------|----------------------|
| 262 000 102 | 262 080 102 |
| 262 000 102 | 262 100 102 |
| 262 000 102 | 262 100 003 |
| 262 000 102 | 262 120 102 |
| 262 000 102 | 262 120 202 |
| 262 000 102 | 262 120 302 |
| 262 000 202 | 262 140 102 |
| 262 000 202 | 262 120 702 |
| 262 000 402 | 262 100 202 |
| 262 000 402 | 262 120 602 |



| R+M Nr. | suitable for R+M Nr. |
|-------------|----------------------|
| 262 000 502 | 262 100 001 |
| 262 000 101 | 262 110 002 |
| 262 120 1 | 262 101 |
| 262 120 1 | 262 120 |
| 262 120 3 | 262 120 902 |

Seal



Rubber ring. For sealing and heightening the motor

| R+M Nr. | ∅ | h |
|-----------|--------|-------|
| 267 158 0 | 144 mm | 20 mm |

Motor cover



Cover for vacuum motors: 262 101, 262 120, 262 120 402, 262 120 502, 262 120 104

| R+M Nr. |
|-------------|
| 262 000 600 |

Symbols h height \varnothing diameter TYP type