

easyfarm365+



LTF

Professional gun with coupling KW.  
Max. 250 bar / 60 l/min / 150 °C

R+M Nr.		
202 620 655	coupling KW	1/2" F swivel



LTF

Professional gun with coupling ST-3100.  
Max. 250 bar / 60 l/min / 150 °C

R+M Nr.		
202 620 650	coupling ST-3100	1/2" F swivel

ST-340 swivels



1/4" F : 1/2" F



Repair kit ST-340

R+M Nr.
200 340 520

R+M Nr.
200 340 150

**LTF - Low Trigger Force** 90 % reduced holding force and 40 % reduced trigger force against usual market guns.

Grips



Grip for lances with  
moulded handle

R+M Nr.
200 009 700



Grip for ST-85  
Push & Pull lances

R+M Nr.
200 009 680

Protector ST-10



1/4" F. Plastic. Stainless  
steel

R+M Nr.
200 010 760

Suitable high pressure hoses are  
on page 154 and 163.

ST-85 Push & Pull lances



Plug KW. Lance stainless steel, vented handle ST-9 380 mm and nozzle protector ST-10 without nozzle. Variable adjustment of spraying angle from 20 to 140°. Especially designed for cleaning of places which are difficult to access. Max. 210 bar / 150 °C

R+M Nr.			
200 085 253	1/4" F NPT	600 mm	plug KW
200 085 613	1/4" F NPT	850 mm	plug KW
200 085 603	1/4" F NPT	1,000 mm	plug KW
200 085 653	1/4" F NPT	1,500 mm	plug KW

Lances



Plug KW. Lance stainless steel, moulded handle 300 mm, valve ST-53 on top, nozzle protector ST-10 with low pressure nozzle and 1/4" M thread for rotating nozzles. Lance without rotating nozzle. Max. 250 bar / 150 °C

R+M Nr.			
200 053 538	300 mm	1/4" M	980 mm plug KW