

Suttner swivels ST-320

Completely stainless steel. Swivel with slide ring as sealing element



3/8" F : 3/8" M. DN 6.

Max. 400 bar / 30 r.p.m. / 90 °C

R+M Nr.	I
200 320 500	48 mm



1/4" F : 1/4" M. DN 6.

Max. 400 bar / 30 r.p.m. / 90 °C

R+M Nr.	I
200 320 550	48 mm



3/8" F : 3/8" M. DN 6.

Max. 400 bar / 30 r.p.m. / 90 °C

R+M Nr.	I
200 320 502	48 mm



Repair kit swivels ST-320

R+M Nr.
200 320 490

Suttner swivels ST-322

Completely stainless steel. Swivel with slide ring as sealing element. Field of application: Hose reels



3/8" F : 3/8" M. DN 10.

Max. 30 r.p.m. / 90 °C

R+M Nr.	P	I
200 322 501	5-100 bar	65 mm
200 322 500	100-400 bar	65 mm



1/2" F : 3/8" M. DN 10.

Max. 30 r.p.m. / 90 °C

R+M Nr.	P	I
200 322 511	5-100 bar	65 mm
200 322 510	100-300 bar	65 mm



1/2" F : 1/2" M. DN 12.

Max. 30 r.p.m. / 90 °C

R+M Nr.	P	I
200 322 521	5-100 bar	67 mm
200 322 520	100-300 bar	67 mm



1/2" F : 1/2" M. DN 12.

Max. 30 r.p.m. / 90 °C

R+M Nr.	P	I
200 322 522	100-300 bar	68 mm



☞ M28 M. DN 12.

For series R+M 434 - R+M 564.

P 100-300 bar. Max. 30 r.p.m. / 90 °C

R+M Nr.	I	☞
200 322 523	79.5 mm	1/2" F
200 322 525	79.5 mm	3/8" F



Repair kit swivels ST-322

R+M Nr.	P
200 322 490	100-300 bar
200 322 491	5-100 bar

Symbols I height ☞ inlet VPE packing unit P pressure