

Raccords tournants 90°, easywash365+

Corps en laiton cadmié. Moyeu en inox. Spécialement conçus pour les bras de lavage



1/4" F : 1/4" M. DN 7.
Max. 275 bar / 30 tr/min / 120 °C

R+M Nr.	∅
562 390 503	46 mm



3/8" F : 1/4" M. DN 7.
Max. 275 bar / 30 tr/min / 120 °C

R+M Nr.	∅
562 390 505	46 mm



3/8" F : 3/8" M. DN 7.
Max. 275 bar / 30 tr/min / 120 °C

R+M Nr.	∅
562 390 507	46 mm



Kit joints pour raccords,
easywash365+

R+M Nr.
750 140 2

Raccords rotatifs, easywash365+

Corps en acier inoxydable / laiton cadmié. Moyeu en acier inoxydable. Sans entretien. DN 6. Raccords tournants particulièrement adaptés pour les raccordements des pistolets, des flexibles, les bras articulés dans les stations de lavage en libre-service



1/4" M : 1/4" F.
Max. 275 bar / 120 °C

R+M Nr.	∅	VPE
562 391 600	63 mm	1
562 391 601	63 mm	25



1/4" M : 3/8" F.
Max. 275 bar / 120 °C

R+M Nr.	∅	VPE
562 391 605	64 mm	1
562 391 606	64 mm	25



3/8" M : 1/4" F.
Max. 275 bar / 120 °C

R+M Nr.	∅	VPE
562 391 610	63 mm	1
562 391 611	63 mm	25



3/8" M : 3/8" F.
Max. 275 bar / 120 °C

R+M Nr.	∅	VPE
562 391 615	64 mm	1
562 391 616	64 mm	25



1/4" F : 1/4" F.
Max. 275 bar / 120 °C

R+M Nr.	∅	VPE
562 391 620	69 mm	1
562 391 621	69 mm	25



3/8" F : 3/8" F.
Max. 275 bar / 120 °C

R+M Nr.	∅	VPE
562 391 625	67 mm	1
562 391 626	67 mm	25



1/4" F : M18 M.
Max. 275 bar / 120 °C

R+M Nr.	∅	VPE
562 391 630	62 mm	1
562 391 631	62 mm	25



1/4" F : M14 M.
Max. 275 bar / 120 °C

R+M Nr.	∅	VPE
562 391 627	62 mm	1
562 391 628	62 mm	25

Raccords tournants 90°, Mosmatic WDG

Corps en laiton cadmié. Moyeu en acier inoxydable. Spécialement conçus pour les bras de lavage



1/4" F : 1/4" M. DN 7.
Max. 150 bar / 30 tr/min / 90 °C

R+M Nr.	∅
750 140 11	46 mm



3/8" F : 1/4" M. DN 7.
Max. 150 bar / 30 tr/min / 90 °C

R+M Nr.	∅
750 140 1	46 mm



Kit joints pour raccords,
Mosmatic WDG

R+M Nr.
750 140 2