

## weeddevil® – Our new device for weed control

- » Ideal for professional service provider in the garden-, municipal and building cleaning industry
- » Completely made out of stainless steel
- » For hot water use of up to 120 °C, 0 - 350 bar
- » Suitable for low and high pressure applications
- » A working width of 400 mm
- » 1/4" nozzles have the ideal spraying angle of 65°

» swivelling application on sloping and vertical areas is possible

**Completely chemical-free!**



**weeddevil®**



ST-2605

**LTF**

Our spray gun ST-2605 with the patented LTF technology is recommended for effortless working.



4 nozzles 1/4" M NPT are required

**At the underside:** concentrated and well-directed hot water without any temperature loss by an optimally designed housing having a perfect cleaning distance.



**Useable at the left or right:** the handle at the side optimises the handling and protects within hot water applications.

4 nozzles 1/4" M are required. 2 robustly industrial castors (260 mm). Max. 120 °C

R+M Nr.	M	castors Ø	working-↔	Ⓒ	Ⓓ	P	°C	Ⓔ	I / ↔
200 097 700	stainl. steel	260 mm	400 mm	1/4" F	4 x 1/4" F	max. 350 bar	120 °C	7.4 kg	1,250 / 530 mm

### Accessories thermometer



Easy mounting with counter plate and screws (incl.), or with back spring. 0 - 120 °C

R+M Nr.	tube-Ø
200 097 420	16 mm (weeddevil)
200 097 425	13 mm (1/4")

### Accessories flow restrictor



Flow restrictor for water reduction. Incl. adapter and nozzles (1,0, 1,1, 1,2, 1,3, 1,4)

R+M Nr.	Ⓒ	Ⓓ
200 097 750	1/4" M	1/4" M / M22 F

**Symbols** M material Ø diameter Ⓒ inlet Ⓓ outlet ↔ width I height °C temperature Ⓔ weight P pressure