

## Safety spectacles, safety goggles and face shields

The accident prevention regulations of the Employer's Liability Insurance Association regarding "the use of high pressure cleaner" (BGV D15) and "tasks with liquid jets" (BGV D26) prescribe that adequate eye and face protection have to be worn in case of an operating pressure of 25 bar and more.

### Safety spectacles



- » Anti-fog, scratch-proof and antistatic polycarbonate lens
- » Integrated side protection. Including neck cord
- » 100 % UV-protection
- » Protected against shock, splinters and solid particle
- » Weight 25 g

R+M Nr.

956 002 817

### Flip-up face shields



- » Anti-fog, scratch-proof and antistatic polycarbonate lens
- » Adjustable headgear
- » 100 % UV-protection
- » Protected against shock, splinters, solid particle and chemical danger (dangerous drops)
- » Weight 200 g

R+M Nr.

956 003 487

### Safety goggles with temples



- » Anti-fog, scratch-proof and antistatic polycarbonate lens
- » Straight temples with adjustable strap. Integrated side protection. Exchangeable plastic foam rim with indirect ventilation
- » Including microfibre cloth
- » 100 % UV-protection
- » Shockproof in case of extreme temperatures
- » Protected against shock, splinters, solid particle and liquids
- » Weight 52 g

R+M Nr.

956 004 828

### Safety goggles with adjustable strap



- » Anti-fog, scratch-proof and antistatic polycarbonate lens
- » Fits over prescription spectacles. Ball-pivot. Fits with respiratory half mask
- » 100 % UV-protection
- » Shockproof in case of extreme temperatures. Resistant to chemical drops, toxic gases, small and big toxic particle, melting metals and hot solids
- » Weight 113 g

R+M Nr.

956 003 067

### Visor



- » Anti-fog, scratch-proof and antistatic polycarbonate lens
- » Visor in connection with safety goggle 956 003 067
- » Shockproof in case of extreme temperatures. Resistant to chemical drops, toxic gases, small and big toxic particle, melting metals and hot solids
- » Weight 73 g

R+M Nr.

956 003 128