

## kommunal365+

## ST-85 Push &amp; Pull lances



Plug ST-3100. Lance stainless steel, vented handle ST-9 380 mm and nozzle protector ST-10 with nozzle. Variable adjustment of spraying angle from 20 to 140°. Especially designed for cleaning of places which are difficult to access. Max. 210 bar / 150 °C

R+M Nr.	ISO	⊖	↔	⊕
200 085 251		1/4" F NPT	600 mm	plug ST-3100
200 085 611		1/4" F NPT	850 mm	plug ST-3100
200 085 601		1/4" F NPT	1,000 mm	plug ST-3100
200 085 651		1/4" F NPT	1,500 mm	plug ST-3100

## Lances



Plug ST-3100. Lance stainless steel, moulded handle 400 mm and nozzle protector ST-10 with nozzle. Max. 400 bar / 150 °C

R+M Nr.	ISO	⊖	↔	⊕
200 000 520	400 mm	1/4" F NPT	1,000 mm	plug ST-3100



Plug ST-3100. Lance stainless steel, moulded handle 300 mm, valve ST-54 aside and nozzle protector ST-10 with low pressure nozzle & thread 1/4" F. Max. 310 bar / 150 °C

R+M Nr.	ISO	⊖	↔	⊕
200 054 506	300 mm	1/4" F NPT	980 mm	plug ST-3100

Symbols ⊖ outlet ⊕ inlet ↔ length ISO insulation