Safety spectacles, safety goggles and face shields

Safety spectacles



- » Anti-fog, scratch-proof and antistatic polycarbonate lens
- » Panoramac field of vision
- » EN166 EN170
- » Protected against shock, splinters and solid particle
- » Weight 30 g

R+M Nr.	
985 600 891 5	



- » Anti-fog and scratch-proof polycarbonate smoke lens
- » Panoramac field of vision
- » 100 % UV-protection
- » Protected against shock, splinters and solid particle
- » Weight 30 g

956 002 820	

Flip-up face shields



- » Anti-fog, scratch-proof and antista- » Anti-fog, scratch-proof and antistatic polycarbonate lens
- » Adjustable headgear
- » 100 % UV-protection
- » Protected against shock, splinters, solid particle and chemical danger (dangerous drops)
- » Weight 200 g

R+M Nr.

956 003 487

Safety goggles with temples



- tic polycarbonate lens
- » Straight temples with adjustable strap. Integrated side protection. Exchangeable plastic foam rim with indirect ventilation
- » Including microfibre cloth
- » 100 % UV-protection
- » Shockproof in case of extreme temperatures
- » Protected against shock, splinters, solid particle and liquids
- » Weight 52 g

956 004 828

R+M Nr.

Visor



- » Anti-fog, scratch-proof and antistatic polycarbonate lens
- » Visor in connection with safety goggle 956 003 067
- » Shockproof in case of extreme temperatures. Resistant to chemical drops, toxic gases, small and big toxic particle, melting metals and hot solids
- » Weight 73 g

R+M Nr.	
956 003 128	

Safety goggles with adjustable strap



- » Anti-fog, scratch-proof and antistatic polycarbonate lens
- » Fits over prescription spectacles.
- » Shockproof in case of extreme temperatures. Resistant to chemical drops, toxic gases, small and big toxic particle, melting metals and hot solids
- » Weight 113 g



- Ball-pivot. Fits with respiratory half
- » 100 % UV-protection

R+M Nr.	
956 003 067	

Gloves

Chemistry Glove Solvex®



Category III -Protection Glove Alpha-Tec® Solvex®37-675.

Very durable nitrile glove for use with hazardous chemicals. The reversed lozenge finish further enhances levels of grip. Cotton-flock liner to

R+M Nr.	VPE	2	size	Θ
956 067 511	1 pair	0.38	11	330 mm
956 167 511	12 pairs	0.38	11	330 mm
956 267 511	144 pairs	0.38	11	330 mm

Protective work gloves Pro-Fit



Category II protective glove, EN 388:2016, Level 3.1.3.1.X

R+M Nr.	VPE	size
980 030	12 pairs	8
980 031	12 pairs	9

- » PU glove, white / white
- » Palm and fingertips with PU coating
- » Polyamide liner
- » Circular knit seamless, knitted cuff
- » Comfortable to wear, breathable
- » Secure grip with excellent sense of touch
- » High abrasion resistance for long service life
- » Excellent fit

adequate eye and face protection have to be worn in case of an operating pressure of 25 bar and more.

The accident prevention regulations of the Employer's Liability

Insurance Association regarding "the use of high pressure cleaner"

(BGV D15) and "tasks with liquid jets" (BGV D26) prescribe that

Symbols VPE packing unit it thickness mm