

COMET high pressure pumps

Premium



Repair kits

01



Valves 6 pieces

02



Seal kits for 3 pistons

03



Oil seal kits

04



Ceramic sockets for 3 pistons

P	☐	U	KW	TYP
276	19.0	1450	10.0	RW 5040S
345	18.0	1450	15.5	TW 4550S
248	27.0	1450	16.5	TW 7036S
172	38.0	1450	12.5	TW 10025S
172	42.5	1450	13.7	TW 11025S

R+M Nr.
172 050 400
172 045 500
172 070 360
172 100 250
172 110 250

R+M Nr.
172 900 002
172 900 003
172 900 005
172 900 005
172 900 005

R+M Nr.
172 900 025
172 900 027
172 900 028
172 900 020
172 900 020

R+M Nr.
172 900 017
172 900 018
172 900 019
172 900 019
172 900 019

R+M Nr.	⌀
172 900 010	18
172 900 012	18
172 900 013	22
172 900 014	25
172 900 014	25

Standard




Repair kits

01



Valves 6 pieces

02



Seal kits for 3 pistons

03



Oil seal kits

04



Ceramic sockets for 3 pistons

P	☐	U	KW	TYP
207	15.0	1450	5.5	FW 4030 S
207	18.8	1450	6.4	FW 5030 S
207	21.0	1450	7.1	FW 5530 S

R+M Nr.
172 040 300
172 050 300
172 055 300

R+M Nr.
172 900 001
172 900 001
172 900 001

R+M Nr.
172 900 023
172 900 024
172 900 024

R+M Nr.
172 900 016
172 900 016
172 900 016

R+M Nr.	⌀
172 900 008	18
172 900 009	20
172 900 009	20

Hot water seal kits are available on request.

COMET motor pumps

Motor pump combinations



Repair kits

01



Valves 6 pieces

02



Seal kits for 3 pistons

03



Oil seal kits

04



Ceramic sockets for 3 pistons

400 V. All models are equipped with a regulation valve, delayed total stop control, pressure gauge, 6 m electric cable and an on-off switch.

P	☐	U	KW	TYP
150	15	1450	4.0	FW2 4025 TS+VA
210	15	1450	5.5	FW2 4030 TS+VA
160	21	1450	5.5	FW2 5523 TS+VA
170	15	1450	4.5	RW 6.15 TS+VA

R+M Nr.
172 040 255
172 040 305
172 055 225
172 006 155

R+M Nr.
172 900 001
172 900 001
172 900 001
172 900 001

R+M Nr.
172 900 023
172 900 023
172 900 024
172 900 026

R+M Nr.
172 900 016
172 900 016
172 900 016
172 900 017

R+M Nr.
172 900 008
172 900 008
172 900 009
172 900 011

Symbols **P** pressure **☐** flow **U** revolutions **KW** kilowatt **TYP** type **⌀** piston diameter **1** height shipment by truck