

## Safety spectacles, safety goggles and face shields

## Safety spectacles



- » Anti-fog, scratch-proof and anti-static polycarbonate lens
- » Panoramic field of vision
- » EN166 - EN170
- » Protected against shock, splinters and solid particle
- » Weight 30 g

R+M Nr.  
985 600 891 5



- » Anti-fog and scratch-proof polycarbonate smoke lens
- » Panoramic field of vision
- » 100 % UV-protection
- » Protected against shock, splinters and solid particle
- » Weight 30 g

R+M Nr.  
956 002 820

## Flip-up face shields



- » Anti-fog, scratch-proof and anti-static polycarbonate lens
- » Adjustable headgear
- » 100 % UV-protection
- » Protected against shock, splinters, solid particle and chemical danger (dangerous drops)
- » Weight 200 g

R+M Nr.  
956 003 487

## Safety goggles with temples



- » Anti-fog, scratch-proof and anti-static polycarbonate lens
- » Straight temples with adjustable strap. Integrated side protection. Exchangeable plastic foam rim with indirect ventilation
- » Including microfibre cloth
- » 100 % UV-protection
- » Shockproof in case of extreme temperatures
- » Protected against shock, splinters, solid particle and liquids
- » Weight 52 g

R+M Nr.  
956 004 828

## Visor



- » Anti-fog, scratch-proof and anti-static polycarbonate lens
- » Visor in connection with safety goggle
- » Shockproof in case of extreme temperatures. Resistant to chemical drops, toxic gases, small and big toxic particle, melting metals and hot solids
- » Weight 73 g

R+M Nr.  
956 003 128

## Safety goggles with adjustable strap



- » Anti-fog, scratch-proof and anti-static polycarbonate lens
- » Fits over prescription spectacles. Ball-pivot. Fits with respiratory half mask
- » 100 % UV-protection
- » Shockproof in case of extreme temperatures. Resistant to chemical drops, toxic gases, small and big toxic particle, melting metals and hot solids
- » Weight 113 g

R+M Nr.  
956 003 067

## Gloves

## Chemistry Glove Solvex®



Category III -Protection Glove Alpha-Tec® Solvex®37-675.  
Very durable nitrile glove for use with hazardous chemicals. The reversed lozenge finish further enhances levels of grip. Cotton-flock liner to the glove

R+M Nr.	VPE	size	⊞
956 067 511	1 pair	0.38	11 330 mm
956 167 511	12 pairs	0.38	11 330 mm
956 267 511	144 pairs	0.38	11 330 mm

## Protective work gloves Pro-Fit



- » PU glove, white / white
- » Palm and fingertips with PU coating
- » Polyamide liner
- » Circular knit seamless, knitted cuff
- » Comfortable to wear, breathable
- » Secure grip with excellent sense of touch
- » High abrasion resistance for long service life
- » Excellent fit

Category II protective glove, EN 388:2016, Level 3.1.3.1.X

R+M Nr.	VPE	size
980 030	12 pairs	8
980 031	12 pairs	9

The accident prevention regulations of the Employer's Liability Insurance Association regarding "the use of high pressure cleaner" (BGV D15) and "tasks with liquid jets" (BGV D26) prescribe that adequate eye and face protection have to be worn in case of an operating pressure of 25 bar and more.

Symbols packing unit thickness mm