

COMET high pressure pumps

Premium



Max. 30 °C

P	←	U	KW	TYP
345	18.0	1,450	15,5	TW 4550S
172	38.0	1,450	12,5	TW 10025S
172	42.5	1,450	13,7	TW 11025S
248	27.0	1,450	16,5	TW 7036 S

R+M Nr.
172 045 500
172 100 250
172 110 250
172 070 360

Repair kits



Valves 6 pieces

R+M Nr.
172 900 003
172 900 005
172 900 005
172 900 005



Seal kits for 3 pistons

R+M Nr.
172 900 027
172 900 020
172 900 020
172 900 028



Oil seal kits

R+M Nr.
172 900 018
172 900 210
172 900 210
172 900 210



Ceramic socket kit for 3 pistons

R+M Nr.
172 900 012
172 900 014
172 900 014
172 900 013



Max. 30 °C

P	←	U	KW	TYP
276	19	1,450	10	RW 5040S

R+M Nr.
172 050 400



Valves 6 pieces

R+M Nr.
172 900 002



Seal kits for 3 pistons

R+M Nr.
172 900 025



Oil seal kits

R+M Nr.
172 900 017



Ceramic socket kit for 3 pistons

R+M Nr.
172 900 010

Standard



Max. 30 °C

P	←	U	KW	TYP
207	15.0	1,450	5,5	FW2 4030 S
207	18.8	1,450	6,4	FW2 5030 S
207	21.0	1,450	7,1	FW2 5530 S

R+M Nr.
172 040 300
172 050 300
172 055 300

Repair kits



Valves 6 pieces

R+M Nr.
172 900 001
172 900 002
172 900 002



Seal kits for 3 pistons

R+M Nr.
172 900 185
172 900 024
172 900 024



Oil seal kits

R+M Nr.
172 900 186
172 900 186
172 900 186



Ceramic socket kit for 3 pistons

R+M Nr.
172 900 008
172 900 009
172 900 009

COMET motor pumps

Motor pump combinations*



400 V. All models are equipped with a regulation valve **, delayed total stop control, pressure gauge, 6 m electric cable and an on-off switch. Ⓢ 3/4" M Ⓢ M22 M. Max. 30 °C

P	←	U	KW	TYP
150	15	1,450	4.0	FW2 4025 TS+VA
210	15	1,450	5.5	FW2 4030 TS+VA
160	21	1,450	5.5	FW2 5523 TS+VA
170	15	1,450	4.5	RW 6.15 TS+VA

R+M Nr.
172 040 255
172 040 305
172 055 225
172 006 155

Repair kits



Valves 6 pieces

R+M Nr.
172 900 001
172 900 001
172 900 002
172 900 001




Seal kits for 3 pistons

R+M Nr.
172 900 185
172 900 185
172 900 024
172 900 026



Oil seal kits (7 pieces)

R+M Nr.
172 900 186
172 900 186
172 900 186
172 900 017



Ceramic sockets for 3 pistons

R+M Nr.	Ⓢ
172 900 008	18
172 900 008	18
172 900 009	20
172 900 011	20

Hot water seal kits are available on request.

* with pump FW2 from 2013

** Setting up of a regulation valve: page 62

Symbols P pressure ← flow U revolutions KW kilowatt TYP type Ⓢ piston diameter shipment by truck Ⓢ thread I height