High pressure equipment

BERTOLINI high pressure pumps

Pump



Repair kits





02

Seal kit

Seal kits for 3

pistons

03

Oil seal kit for 1 piston

04



05

Ceramic socket Fastening for 1 piston



06

screw for 1 piston

P	—	U	KW	TYP
210	15	1,450	6.1	TTL 1520
210	21	1,450	8.6	TTL 2120
300	13	1,450	7.6	TTL 1330
300	20	1,450	11.5	TTL 2030

R+M Nr. 177 015 200 177 021 200 177 013 300 177 020 300

R+M Nr. 177 698 679 73 177 698 679 73 177 698 679 73 177 698 679 73

Repair kits

Valves 6 pieces

01

Valves 6 pieces

R+M Nr. 177 698 369 73 177 698 369 73 177 698 349 73 177 698 349 73

R+M Nr. 177 698 399 73 177 698 399 73 177 698 339 73 177 698 339 73

R+M Nr. 177 698 729 73 177 698 729 73 177 698 729 73 177 698 729 73

R+M Nr. 177 600 091 82 177 600 091 82 177 600 551 82 177 600 551 82

R+M Nr. 177 600 720 02 177 600 720 02 177 600 735 12 177 600 735 12

Hawk high pressure pumps

02

Pump



TYP

NMT 1520R

NMT 2120R

XLT 2530IR

XLT 3025IR

(KW)

15 1,450 5.7

240 30 1,450 14.2

1,450 7.9 300 24 1,450 14.1

_	R+M Nr.	,
	174 015	20
	174 021	20
	174 024	3(
	174 030	2
	474005	

R+M Nr. 174 190 554 3 00 00 174 190 554 3 00 174 190 568 7 174 190 568 7 40 170 35 1,450 11.2 XLT 3517IR 174 035 170 174 190 568 6



Seal kit for 3 pistons

R+M Nr.

174 190 557 8

174 190 557 8

174 190 567 0

174 190 585 2

174 190 585 3



Seal kits for 3 pistons

R+M Nr.

174 260 077

174 260 077

174 260 126

174 260 125

174 260 113



Oil seal kit for 3 pistons



05

Ceramic socket for 1 piston, complete

complete		
R+M Nr.		
174 260 107		
174 260 107		
174 260 130		
174 260 129		
174 260 117		

Pump accessories

Wall bracket

200

200

21



Stainless steel. 200 x 200 x 150 mm. Suitable for our motor-pump units with AR HPV

R+M Nr.
105 000 021



Stainless steel. 280 x 280 x 260 mm. Suitable for our motor-pump units 3/4/5.5 and 7.5 KW with 3 / 4 and 5.5 KW

With 57 Tune	1 3.3 1111
R+M Nr.	
105 000 022	



Stainless steel. 270 x 270 x 500 mm. Capacity: 80 kg. Suitable for our motor-pump units with

R+M Nr.	
105 000 020	

Vibrationdamper



Rubber buffer type A. M10 x 28. Incl. Screws and washers. Steel or stainless steel and elastic natural rubber 55°. Spring stiffness: 500 N/mm. Load: 2,000 N

R+M Nr.	(<u>M</u>)	(VPE)
105 000 101	steel	4 pieces
105 000 104	stainless steel	4 pieces

Symbols P pressure — flow U revolutions KW kilowatt TYP type KO piston diameter O thread VPE packing unit M material