


Umlaufventile

VB75



☉ = Eingang 1/2" IG. ☉ = Ausgang 3/8" IG.
Umlaufventil mit Hohlsschraube. Banjo-Anschluss.
X: 19 mm. Y: 62-73 mm. Passend IP50, IP44, IP47,
IP60, IP63 / Speck NP16. Max. 250 bar / 90 °C

R+M Nr.	☉	☉
532 093 0		30 l/min

VB85



☉ = Eingang 1/2" IG. ☉ = Ausgang 1/2" IG.
☉ = Bypass 1/2" IG. Max. 90 °C

R+M Nr.	☉	☉	☉
532 851 6	max. 160 bar		80 l/min
532 852 8	max. 280 bar		80 l/min

Rep. Kit VB85



R+M Nr.
532 851 62

VB80



☉ = Eingang 1/2" IG. ☉ = Ausgang 1/2" IG.
☉ = Bypass 1/2" IG.
Edelstahl.
Max. 90 °C

R+M Nr.	☉	☉
532 802 84	max. 280 bar	80 l/min

VB80/150



☉ = Eingang 1/2" IG. ☉ = Ausgang 1/2" IG.
☉ = Bypass 1/2" IG. ☉ = Manometer 1/4" IG.
Max. 90 °C

R+M Nr.	☉	☉	☉
532 801 50	max. 150 bar		80 l/min

VB53/500



☉ = Eingang 1/2" IG. ☉ = Ausgang 1/2" IG. ☉ = Bypass 1/2" IG.
Max. 90 °C

R+M Nr.	☉	☉
532 535 00	max. 500 bar	80 l/min

VB26



☉ = Eingang 1/2" IG. ☉ = Ausgang 1/2" IG.
☉ = Bypass 1/2" IG. Edelstahl.
Max. 90 °C

R+M Nr.	☉	☉
532 262 80	max. 280 bar	80 l/min

VRT100/190



☉ = Eingang 1/2" IG. ☉ = Ausgang 1/2" IG.
☉ = Bypass 1/2" IG.
Max. 90 °C

R+M Nr.	☉	☉
532 056 0	max. 190 bar	100 l/min

Symbole ☉ Eingang ☉ Ausgang ☉ Bypass ☉ Manometer ☉ Durchfluss ☉ Druck