

## Regulation valves

VB75



☉ = inlet 1/2" F. ☉ = outlet 3/8" F. Regulation valve with banjo-bolt. X: 19 mm. Y: 62-73 mm. Suitable for IP50, IP44, IP47, IP60, IP63 / Speck NP16. Max. 250 bar / 90 °C

| R+M Nr.   | P | ☉        |
|-----------|---|----------|
| 532 093 0 |   | 30 l/min |

VB85



☉ = inlet 1/2" F. ☉ = outlet 1/2" F. [BP] = bypass 1/2" F. Max. 90 °C

| R+M Nr.   | P            | ☉        |
|-----------|--------------|----------|
| 532 851 6 | max. 160 bar | 80 l/min |
| 532 852 8 | max. 280 bar | 80 l/min |

Rep. Kit VB85



| R+M Nr.    |
|------------|
| 532 851 62 |

VB80



☉ = inlet 1/2" F. ☉ = outlet 1/2" F. [BP] = bypass 1/2" F. Stainless steel. Max. 90 °C

| R+M Nr.    | P            | ☉        |
|------------|--------------|----------|
| 532 802 84 | max. 280 bar | 80 l/min |

VB80/150



☉ = inlet 1/2" F. ☉ = outlet 1/2" F. [BP] = bypass 1/2" F. [MN] = pressure gauge 1/4" F. Max. 90 °C

| R+M Nr.    | P            | ☉        |
|------------|--------------|----------|
| 532 801 50 | max. 150 bar | 80 l/min |

VB53/500



☉ = inlet 1/2" F. ☉ = outlet 1/2" F. [BP] = bypass 1/2" F. Max. 90 °C

| R+M Nr.    | P            | ☉        |
|------------|--------------|----------|
| 532 535 00 | max. 500 bar | 80 l/min |

VB26



☉ = inlet 1/2" F. ☉ = outlet 1/2" F. [BP] = bypass 1/2" F. Stainless steel. Max. 90 °C

| R+M Nr.    | P            | ☉        |
|------------|--------------|----------|
| 532 262 80 | max. 280 bar | 80 l/min |

VRT100/190



☉ = inlet 1/2" F. ☉ = outlet 1/2" F. [BP] = bypass 1/2" F. Max. 90 °C

| R+M Nr.   | P            | ☉         |
|-----------|--------------|-----------|
| 532 056 0 | max. 190 bar | 100 l/min |

Symbols ☉ inlet ☉ outlet [BP] bypass [MN] pressure gauge ☉ flow P pressure