

Regulation valves

VB350



Ⓒ = inlet 3/8" F. Ⓓ = outlet 3/8" F. [BP] = bypass 1/2" F. [MN] = pressure gauge 1/4" F. Regulation valve with switch (IP55) and cable 1,200 mm. Max. 350 bar / 90 °C

R+M Nr.	☰
532 350	40 l/min

VB350



Ⓒ = inlet 3/8" F. Ⓓ = outlet 3/8" F. [BP] = bypass 1/2" F. [MN] = pressure gauge 1/4" F. Max. 350 bar / 90 °C

R+M Nr.	☰
532 340	40 l/min

VB60/600



Ⓒ = inlet 1/2" F. Ⓓ = outlet 1/2" F. [BP] = bypass 1/2" F. Max. 600 bar / 90 °C

R+M Nr.	☰
532 260 0	60 l/min

VB60/600



Ⓒ = inlet 1/2" F. Ⓓ = outlet 1/2" F. [BP] = bypass 1/2" F. Regulation valve with micro switch (IP55) and cable 950 mm. Max. 600 bar / 90 °C

R+M Nr.	☰
532 265 0	60 l/min

Zeromatic 93



Ⓒ = inlet 1/2" F. Ⓓ = outlet 3/8" M. [BP] = bypass 1/2" F. [MN] = pressure gauge 1/4" F. Max. 250 bar / 60 °C

R+M Nr.	☰
170 290 7	40 l/min

Symbols Ⓒ inlet Ⓓ outlet [BP] bypass [MN] pressure gauge ☰ flow TYP type