













Suttner chemical injectors







ST-60				ST-62				Metering valves		Repair kits																																			
																																													
Injector without metering valve. Max. 250 bar / 60 °C				Injector without metering valve. Adjustable bypass allows big water flow rates without reduction of the water pressure. Max. 250 bar / 60 °C				Valve for Suttner injector. Hose tail 6 mm		Chemical check valve. Hose tail 6 mm																																			
<table border="1"> <thead> <tr> <th>R+M Nr.</th> <th>G</th> <th>F</th> <th>D</th> </tr> </thead> <tbody> <tr> <td>200 060 600</td> <td>3/8" M</td> <td>3/8" F</td> <td>1.8 mm</td> </tr> <tr> <td>200 060 610</td> <td>3/8" M</td> <td>3/8" F</td> <td>2.1 mm</td> </tr> <tr> <td>200 060 620</td> <td>3/8" M</td> <td>3/8" F</td> <td>2.4 mm</td> </tr> </tbody> </table>				R+M Nr.	G	F	D	200 060 600	3/8" M	3/8" F	1.8 mm	200 060 610	3/8" M	3/8" F	2.1 mm	200 060 620	3/8" M	3/8" F	2.4 mm	<table border="1"> <thead> <tr> <th>R+M Nr.</th> <th>G</th> <th>F</th> <th>D</th> </tr> </thead> <tbody> <tr> <td>200 062 500</td> <td>3/8" F</td> <td>3/8" F</td> <td>1.6 mm</td> </tr> </tbody> </table>				R+M Nr.	G	F	D	200 062 500	3/8" F	3/8" F	1.6 mm	<table border="1"> <thead> <tr> <th>R+M Nr.</th> <th></th> </tr> </thead> <tbody> <tr> <td>050 000 370</td> <td>1</td> </tr> <tr> <td>200 061 500</td> <td>2</td> </tr> </tbody> </table>		R+M Nr.		050 000 370	1	200 061 500	2	<table border="1"> <thead> <tr> <th>R+M Nr.</th> <th></th> </tr> </thead> <tbody> <tr> <td>200 060 725</td> <td></td> </tr> </tbody> </table>		R+M Nr.		200 060 725	
R+M Nr.	G	F	D																																										
200 060 600	3/8" M	3/8" F	1.8 mm																																										
200 060 610	3/8" M	3/8" F	2.1 mm																																										
200 060 620	3/8" M	3/8" F	2.4 mm																																										
R+M Nr.	G	F	D																																										
200 062 500	3/8" F	3/8" F	1.6 mm																																										
R+M Nr.																																													
050 000 370	1																																												
200 061 500	2																																												
R+M Nr.																																													
200 060 725																																													

Suttner foam injectors

ST-60.1				ST-60.1				ST-60.1																											
																																			
Coupling ST-45-250 : plug ST-45-250. Injector with metering valve, suction hose 1000 mm and suction filter ST-31. Max. 250 bar / 60 °C				Injector without metering valve. Max. 250 bar / 60 °C				M22 F : M22 M. Injector with metering valve, suction hose 1000 mm and suction filter ST-31. Max. 250 bar / 60 °C																											
<table border="1"> <thead> <tr> <th>R+M Nr.</th> <th></th> <th>D</th> </tr> </thead> <tbody> <tr> <td>200 060 750</td> <td></td> <td>1.6 mm</td> </tr> </tbody> </table>				R+M Nr.		D	200 060 750		1.6 mm	<table border="1"> <thead> <tr> <th>R+M Nr.</th> <th>G</th> <th>F</th> <th>D</th> </tr> </thead> <tbody> <tr> <td>200 060 700</td> <td>3/8" M</td> <td>3/8" F</td> <td>1.6 mm</td> </tr> <tr> <td>200 060 710</td> <td>3/8" M</td> <td>3/8" F</td> <td>1.8 mm</td> </tr> </tbody> </table>				R+M Nr.	G	F	D	200 060 700	3/8" M	3/8" F	1.6 mm	200 060 710	3/8" M	3/8" F	1.8 mm	<table border="1"> <thead> <tr> <th>R+M Nr.</th> <th></th> <th>D</th> </tr> </thead> <tbody> <tr> <td>200 060 760</td> <td></td> <td>1.6 mm</td> </tr> </tbody> </table>				R+M Nr.		D	200 060 760		1.6 mm
R+M Nr.		D																																	
200 060 750		1.6 mm																																	
R+M Nr.	G	F	D																																
200 060 700	3/8" M	3/8" F	1.6 mm																																
200 060 710	3/8" M	3/8" F	1.8 mm																																
R+M Nr.		D																																	
200 060 760		1.6 mm																																	
Metering valves				Repair kits																															
		Valve for Suttner injector. Hose tail 6 mm				Chemical check valve. Hose tail 6 mm																													
		<table border="1"> <thead> <tr> <th>R+M Nr.</th> <th></th> </tr> </thead> <tbody> <tr> <td>050 000 370</td> <td>1</td> </tr> <tr> <td>200 061 500</td> <td>2</td> </tr> </tbody> </table>		R+M Nr.		050 000 370	1	200 061 500	2			<table border="1"> <thead> <tr> <th>R+M Nr.</th> <th></th> </tr> </thead> <tbody> <tr> <td>200 060 725</td> <td></td> </tr> </tbody> </table>		R+M Nr.		200 060 725																			
R+M Nr.																																			
050 000 370	1																																		
200 061 500	2																																		
R+M Nr.																																			
200 060 725																																			

The suitable foam lances are presented on pages 301-303.

Accumulator

																										
																										
Volume 0.07 liter. Max. 80 °C		Volume 0.21 liter. Max. 85 °C		Volume 0.35 liter. Max. 85 °C																						
<table border="1"> <thead> <tr> <th>R+M Nr.</th> <th>O</th> <th>P</th> </tr> </thead> <tbody> <tr> <td>189 307 0</td> <td>M14 M</td> <td>15 - 200 bar</td> </tr> </tbody> </table>		R+M Nr.	O	P	189 307 0	M14 M	15 - 200 bar	<table border="1"> <thead> <tr> <th>R+M Nr.</th> <th>O</th> <th>P</th> </tr> </thead> <tbody> <tr> <td>189 321 0</td> <td>M16 M</td> <td>25 - 220 bar</td> </tr> <tr> <td>189 321 2</td> <td>3/8" M</td> <td>25 - 220 bar</td> </tr> </tbody> </table>		R+M Nr.	O	P	189 321 0	M16 M	25 - 220 bar	189 321 2	3/8" M	25 - 220 bar	<table border="1"> <thead> <tr> <th>R+M Nr.</th> <th>O</th> <th>P</th> </tr> </thead> <tbody> <tr> <td>189 211 0 *</td> <td>3/8" F</td> <td>40 - 210 bar</td> </tr> </tbody> </table>		R+M Nr.	O	P	189 211 0 *	3/8" F	40 - 210 bar
R+M Nr.	O	P																								
189 307 0	M14 M	15 - 200 bar																								
R+M Nr.	O	P																								
189 321 0	M16 M	25 - 220 bar																								
189 321 2	3/8" M	25 - 220 bar																								
R+M Nr.	O	P																								
189 211 0 *	3/8" F	40 - 210 bar																								

* Accumulator must be filled with nitrogen