

## easyfoam365+ injectors by Suttner

## Injectors ST-160



Coupling ST-45-250 stainless steel : plug ST-45-250 stainless steel. Injector with suction hose 2000 mm and suction filter ST-31. The chemical dosing is adjusted by 8 exchangeable nozzle inserts (0.5 - 1.5 mm).  
Max. 250 bar / 90 °C

R+M Nr.	D
200 160 815	1.2 mm
200 160 816	1.3 mm
200 160 817	1.4 mm
200 160 818	1.5 mm
200 160 819	1.6 mm
200 160 820	1.7 mm
200 160 821	1.8 mm
200 160 822	1.9 mm
200 160 823	2.0 mm
200 160 824	2.1 mm
200 160 825	2.2 mm
200 160 826	2.3 mm



Coupling ST-45-250 nickel-plated brass : plug ST-45-250 zinc-plated steel. Injector with suction hose 2000 mm and suction filter ST-31. The chemical dosing is adjusted by 8 exchangeable nozzle inserts (0.5 - 1.5 mm).  
Max. 250 bar / 90 °C

R+M Nr.	D
200 160 830	1.2 mm
200 160 831	1.3 mm
200 160 832	1.4 mm
200 160 833	1.5 mm
200 160 834	1.6 mm
200 160 835	1.7 mm
200 160 836	1.8 mm
200 160 837	1.9 mm
200 160 838	2.0 mm
200 160 839	2.1 mm
200 160 840	2.2 mm
200 160 841	2.3 mm



M22 F : M22 M. Injector with suction hose 2000 mm and suction filter ST-31. The chemical dosing is adjusted by 8 exchangeable nozzle inserts (0.5 - 1.5 mm).  
Max. 350 bar / 90 °C

R+M Nr.	D
200 160 753	1.2 mm
200 160 754	1.3 mm
200 160 750	1.4 mm
200 160 751	1.5 mm
200 160 752	1.6 mm
200 160 755	1.7 mm
200 160 756	1.8 mm
200 160 757	1.9 mm
200 160 758	2.0 mm
200 160 759	2.1 mm
200 160 760	2.2 mm
200 160 761	2.3 mm