


Motor protection switches

Type OKN



K F



Housing for type OKN


R+M Nr.	working range
901 510	6.3 - 10.0 A
901 516	10.0 - 16.0 A
901 522	16.0 - 22.0 A
901 527	22.0 - 27.0 A

R+M Nr.	(M)
901 540	plastic

Time hour meter




cutout



Meter with clip

R+M Nr.	(V)
915 102 4	24 V ~
915 122 0	230 V ~

Type OKE 2



Housing for type OKE 2

R+M Nr.	working range
901 610	6.3 - 10.0 A
901 616	10.0 - 16.0 A
901 625	16.0 - 25.0 A

R+M Nr.	(M)
901 630	plastic

Inrush current limiter

gefistart




K A

Fully electronic limiter. Rugged splashproof housing IP5. Designed for the reduction of inrush current in case of 1-phase alternating current and for the protection of circuit safety.

R+M Nr.	(A)	(W)	(V)
901 350 0	16 A	3500 W	230 V ~

Remote thermometers

With contact probe and adjustable knob



1/2" M. Contact 5 A - 250 V (AC1). Indication of temperature 0 - 120 °C


R+M Nr.	working range	tube length
910 20	0 - 80 °C	1000 mm

Remote thermostats

Emerson 1536



F




M14 x 1 M. Contact 16 A - 380 V (AC1)

R+M Nr.	working range	tube length
910 16	0 - 160 °C	1550 mm

Probe with screw



K




3/8" M. Contact 16 A - 380 V (AC1)

R+M Nr.	working range	tube length
910 12	30 - 150 °C	1520 mm
910 13	0 - 152 °C	920 mm

Emerson 8654



W



3/8" M. Contact 16 A - 380 V (AC1)

R+M Nr.	working range	tube length
910 15	30 - 150 °C	1550 mm

Symbols (M) material (A) ampere (V) voltage (W) watt (∅) diameter (KW) kilowatt (TYP) type (truck) shipment by truck