


**Motor protection switches**

**Type OKN**




Housing for type OKN

R+M Nr.	working range
901 516	10.0 - 16.0 A
901 522	16.0 - 22.0 A
901 527	22.0 - 27.0 A

R+M Nr.	(M)
901 540	plastic

**Type WIMEX**




Housing for type WIMEX, IP55

R+M Nr.	working range
901 710	6.3 - 10.0 A
901 716	10.0 - 16.0 A
901 720	16.0 - 20.0 A
901 725	20.0 - 25.0 A

R+M Nr.	(M)
901 730	plastic

**Time hour meter**




Meter with clip

R+M Nr.	(V)
915 102 4	24 V ~
915 122 0	230 V ~
915 140 0	400 V ~

**Remote thermometers**

**With contact probe and adjustable knob**





1/2" M. Contact 5 A - 250 V (AC1). Indication of temperature 0 - 120 °C

R+M Nr.	working range	tube length
910 20	0 - 80 °C	1,000 mm

**Remote thermostats**


**Emerson 1536**



M14 x 1 M. Contact 16 A - 380 V (AC1)

R+M Nr.	working range	tube length
910 16	0 - 160 °C	1,550 mm


**Probe with screw**



3/8" M. Contact 16 A - 380 V (AC1)

R+M Nr.	working range	tube length
910 12	30 - 150 °C	1,520 mm
910 13	0 - 152 °C	920 mm


**Emerson 8654**



3/8" M. Contact 16 A - 380 V (AC1)

R+M Nr.	working range	tube length
910 15	30 - 150 °C	1,550 mm

**Probe pocket PS1**



Brass. Max. 280 bar / 160 °C

R+M Nr.
178 290 260 35