

Removable screw connections

Male thread : male thread



Stainless steel

AG : AG	R+M Nr.	P
1/2" : 1/2"	574 812 009	max. 15 bar 67
3/4" : 3/4"	574 834 009	max. 15 bar 73

Quick screw couplings ST-740 and nipples ST-741

Quick screw couplings ST-740 and nipples ST-741



M24 F : M.
Max. 700 bar / 150 °C



M24 F : M.
Max. 700 bar / 150 °C



M : M24 M.
Max. 700 bar / 150 °C



M24 M : M24 M.
Max. 700 bar / 150 °C

⊙	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.
3/8"	200 740 501	200 740 601	200 741 501	
1/2"	200 740 503		200 741 503	
M24				200 741 600



M24 F : F.
Max. 700 bar / 150 °C



M24 F : F.
Max. 700 bar / 150 °C



F : M24 M.
Max. 700 bar / 150 °C

⊙	R+M Nr.	R+M Nr.	R+M Nr.
1/4"	200 740 504	200 740 604	200 741 504
3/8"	200 740 502	200 740 602	200 741 502
M16x1	200 740 506		

Seals



O-ring - ST-740

R+M Nr.
050 000 408



O-ring - ST-741

R+M Nr.
050 001 000



Back ring - ST-740

R+M Nr.
050 000 407

Symbols ⊙ female thread AG male thread ⊖ length ⊕ height ⊙ thread ⊗ diameter TYP type