

Suttner quick screw swivel couplings ST-44

Quick screw coupling : male thread



M22 F : M. Max. 400 bar / 150 °C

K

⊙
1/4"
3/8"
1/2"
M18
M22

R+M Nr.	ⓘ
568 00	49 mm
568 25	70 mm
568 26	73 mm
568 30	76 mm
568 10	76 mm



M21 F : M. Max. 400 bar / 150 °C

W

R+M Nr.	ⓘ
568 50	49 mm
568 70	46 mm



M22 F : M. Max. 200 bar

R+M Nr.	ⓘ
200 044 510	49 mm

M22 F : M22 M. Stainless steel.
Max. 400 bar / 150 °C

K

⊙
M22

R+M Nr.	ⓘ
568 19	56 mm

Quick screw coupling : female thread



M22 F : F. Max. 400 bar / 150 °C

K

⊙
1/4"
3/8"

R+M Nr.	ⓘ
568 15	67 mm



M22 F : F. Max. 400 bar / 150 °C

K

R+M Nr.	ⓘ
568 20	68 mm



M21 F : F. Max. 400 bar / 150 °C

W

R+M Nr.	ⓘ
568 80	67 mm

Seals ST-44



O-ring

R+M Nr.	VPE
050 000 651	1
568 009 100	100



U-ring

R+M Nr.
050 000 379



O-ring (back)

R+M Nr.	TYP
568 011	small
568 010	big



Back ring

R+M Nr.	VPE
050 001 511	1
568 008 100	100



Seal kit

R+M Nr.
568 001 1

Symbols ⓘ height ⊙ thread VPE packing unit TYP type