

## Gegennippel zu Hand- und Drehverschraubungen

Außengewinde : Innengewinde



M22 AG : IG. Messing. Max. 400 bar

Ø	R+M Nr.	i
1/8"	565 10	29
1/4"	565 20	29
3/8"	565 40	29
1/2"	565 65	29
M16	565 90 *	34
M18		
M22	565 66	33

R+M Nr.	i
565 10	29
565 20	29
565 40	29
565 65	29
565 90 *	34
565 66	33



M21 AG : IG. Messing. Max. 400 bar

R+M Nr.	i
567 10	30
567 20	29
567 40	29
567 60 *	30



1/2" AG : IG. Messing. Max. 400 bar

R+M Nr.	i
567 80	29

M22 AG : IG. Messing.  
Langbohrung. Max. 400 bar

Ø	R+M Nr.	i
1/4"	565 251	40
3/8"	565 401	40
1/2"		

R+M Nr.	i
565 251	40
565 401	40

M22 AG : IG. Messing.  
Innensechskant. Max. 400 bar

R+M Nr.	i
565 80	38

M22 AG : IG. Edelstahl.  
Max. 500 bar

R+M Nr.	i
565 29	29
565 49	29
565 659	30

## Gegennippel zu Hand- und Drehverschraubungen

Außengewinde : Außengewinde

M22 AG : AG. Messing.  
Max. 400 bar

Ø	R+M Nr.	i
1/4"	565 30	29 mm
3/8"	565 50	29 mm
1/2"	565 60	29 mm

R+M Nr.	i
565 30	29 mm
565 50	29 mm
565 60	29 mm

M22 AG : AG mit Konus (AGR).  
Messing. Max. 400 bar

R+M Nr.	i
565 301	31,5 mm
565 501	31,5 mm

R+M Nr.	i
565 301	31,5 mm
565 501	31,5 mm

M21 AG : AG. Messing.  
Max. 400 bar

R+M Nr.	i
567 30	32 mm
567 50	32 mm

R+M Nr.	i
567 30	32 mm
567 50	32 mm

M22 AG : AG. Messing.  
Langbohrung. Max. 400 bar

Ø	R+M Nr.	i
1/4"	565 311	40 mm
3/8"	565 511	40 mm
1/2"		

R+M Nr.	i
565 311	40 mm
565 511	40 mm

M22 AG : AG. Edelstahl.  
Max. 500 bar

R+M Nr.	i
565 39	29 mm
565 59	29 mm
565 69	29 mm

R+M Nr.	i
565 39	29 mm
565 59	29 mm
565 69	29 mm

M22 AG : AG. Edelstahl.  
Max. 400 bar

R+M Nr.	i
565 312 9	42 mm

R+M Nr.	i
565 312 9	42 mm

\* Restposten