

## High pressure quick couplings

## Couplings CEJN 322 and plug



Coupling : F. Chrome-plated brass /  
chrome-plated steel.  
Max. 200 bar / 100 °C



Plug : F.  $\varnothing$  12 mm. Nickel-plated  
steel. Max. 200 bar / 100 °C

$\varnothing$	DN
1/4"	7.4
3/8"	7.4

R+M Nr.	I
552 001	48 mm
552 002	50 mm

R+M Nr.	I
552 101	36 mm
552 102	38 mm

## Couplings SP-20 250 bar and plug



Coupling : F. Brass.  
Max. 250 bar / 100 °C



Coupling : M. Brass.  
Max. 250 bar / 100 °C



Plug : F.  $\varnothing$  14.8 mm. Zinc-plated  
steel. Max. 250 bar / 100 °C

$\varnothing$	DN
1/4"	8.0
3/8"	8.0
1/2"	8.0

R+M Nr.	I
550 10	41 mm
550 30	42 mm

R+M Nr.	I
550 20	43 mm

R+M Nr.	I
551 11	40 mm
551 10	40 mm



Plug : M.  $\varnothing$  14.8 mm. Zinc-plated  
steel. Max. 250 bar / 100 °C



O-ring. [TYP] SP-20. 13.1x2.6.  
Max. 250 bar / 100 °C

$\varnothing$	DN
3/8"	8.0

R+M Nr.	I
551 20	43 mm

R+M Nr.	I
790 60	