

ST-247 coupling system

TR22 adapters (old : new)



TR22 M : M22 F. Alternative to adapter 2+3. Brass. Max. 400 bar / 150° C.

| |
|-------------|
| R+M Nr. |
| 561 022 220 |



TR22 M : M22 F QSV. Brass. Swivel. Alternative to adapter 2+3. Max. 400 bar / 150° C.

| |
|-------------|
| R+M Nr. |
| 568 022 220 |



TR22 M : M 22 F QSV. Brass. Swivel. Alternative to adapter 2+3. Max. 400 bar / 150° C.

| |
|-------------|
| R+M Nr. |
| 568 022 221 |



TR22 F : 3/8" F. Swivel. Brass. Alternative to adapter 12. Incl. 1 heat resistant cap. Max. 400 bar / 150° C.

| |
|-------------|
| R+M Nr. |
| 200 301 110 |



TR22 F : M22 M. Swivel. Brass. Alternative to adapter 12. Incl. 1 heat resistant cap. Max. 400 bar / 150° C.

| |
|-------------|
| R+M Nr. |
| 200 301 100 |



3/8" M : TR22 M. Brass. Max. 400 bar / 150° C.

| |
|-------------|
| R+M Nr. |
| 010 003 041 |



TR22 F : TR22 M. Brass. Max. 400 bar / 150° C.

| |
|-------------|
| R+M Nr. |
| 200 247 250 |



TR22 F : 3/8" M. Alternative to adapter 6. Brass. Max. 400 bar / 150° C.

| |
|---------|
| R+M Nr. |
| 565 683 |



TR22 F : 3/8" F. Alternative to adapter 6. Brass. Max. 400 bar / 150° C.

| |
|---------|
| R+M Nr. |
| 565 684 |



TR22 F : M22 M. Alternative to adapter 6. Brass. Max. 400 bar / 150° C.

| |
|---------|
| R+M Nr. |
| 565 681 |



TR22 F : Plug coupling Ø 11 mm. Brass/stainless steel. Max. 400 bar / 150° C.

| |
|---------|
| R+M Nr. |
| 565 688 |

TR20 adapters lances



TR20 F : M18 M. Alternative to adapter 8. Brass. Max. 400 bar / 150° C.

| |
|---------|
| R+M Nr. |
| 565 686 |




TR20 F : 1/4" M. Stainless steel. Max. 400 bar / 150° C.

| |
|------------|
| R+M Nr. |
| 565 685 19 |



M22 F : TR20 M. Alternative to adapter 7. Brass. Max. 400 bar / 150° C.

| |
|---------|
| R+M Nr. |
| 565 685 |



M18 x 1.5 IG : TR20 AG. Alternative to adapter 7. Brass. Max. 400 bar / 150° C.


| |
|---------|
| R+M Nr. |
| 565 687 |

Hose connectors



TR22 M. Alternative to adapter 9. Brass. Max. 400 bar.

| |
|---------|
| R+M Nr. |
| 569 22 |



TR 22 M : M22 x 1,5 M. Alternative to adapter 1. Brass. Max. 400 bar.

| |
|---------|
| R+M Nr. |
| 569 23 |

Wrench



| | |
|-------------|----|
| R+M Nr. | SW |
| 100 000 235 | 27 |