

Schlauchadapter



Steckkupplung 10 mm : 3/8" AG.
Max. 400 bar

R+M Nr.	
559 910 1	



Steckkupplung 11 mm. Max. 400 bar

R+M Nr.	
559 911 12	1/2" AG
559 911 38	3/8" AG
559 911 22	M22 AG
559 911 23	HV M22



M22 IG : M22 AG. K 2000. Messing.
Max. 400 bar

R+M Nr.	
565 66	



Stecknippel 10 mm : M22 AG.
Max. 250 bar

R+M Nr.	
559 910 2	



O-Ring

R+M Nr.	
790 55	10 mm



M24 AG : AG. Messing *.
Max. 400 bar

R+M Nr.	
318 241 8	M18
318 242 1	M21



M27 AG : AG. Messing *.
Max. 400 bar

R+M Nr.	
318 271 8	M18
318 272 1	M21



M24 AG : 3/8" IG. Messing *.
Max. 400 bar

R+M Nr.	
318 24	



M27 AG : 3/8" IG. Messing *.
Max. 400 bar

R+M Nr.	
318 27	



Kupfer Dichtungsscheibe. K 2000

R+M Nr.	
781 519 1	18,8 mm



Stützring

R+M Nr.	
790 58	10 mm



O-Ring

R+M Nr.	
791 42	M24



O-Ring

R+M Nr.	
903 598 00	M27



O-Ring. 10x2,2. Perbunan

R+M Nr.	
790 25	1
790 251 00	100



O-Ring. 9,5x2

R+M Nr.	
050 002 456	1

Reduziernippel

Innengewinde : Außengewinde



Messing. Max. 400 bar

R+M Nr.	
710 100 032	
710 100 033	

IG : AG	
1/4" : M12x1	
M12x1 : 1/4"	

* nicht zulässig für patentierte WAP / Venturi - Einsätze