


High pressure hoses for hose reels



Hoses with single wire braid and *smooth* cover

TYP	DN	P	°C	↔	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.
Flexy	6	300 bar	100 °C	10 m	390 036 815	390 035 210				390 010 281 0		
				15 m	390 035 215			390 010 081 5		390 010 281 5		

Hoses with single wire braid and *wrapped* cover

TYP	DN	P	°C	↔	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.
1SN	6	250 bar	150 °C	10 m	330 136 810					330 110 281 0		
				15 m	330 136 815			330 110 081 5		330 110 281 5		
1SN	8	210 bar	150 °C	20 m							340 100 820 1	
				30 m							340 100 830 1	

Hoses with double wire braid and *wrapped* cover

TYP	DN	P	°C	↔	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	R+M Nr.	
2SC	6	400 bar	150 °C	10 m	335 136 810								
				15 m	335 136 815								
				20 m	335 136 820								
2SC	8	400 bar	150 °C	10 m	345 136 810								
				15 m	345 136 815								
				20 m	345 136 820						345 100 820 1	346 100 820 1	
				30 m						345 100 830 1			
				40 m						345 100 840 1			

Symbols ∅ diameter DN nominal diameter P pressure °C temperature ↔ length TYP type