

CARWASH COMFORT - you are invited to experience our blue hose wonder in DN 8!

High-tensile polyester reinforcing, working pressure of up to 200 bar. DN 8. -40 °C – +60 °C, -40 °F – +140 °F



1/4" : 1/4"		3/8" : 3/8"		M14 : M14		M18 : M18		3/8" : 3/8"	
Female thread (DKR)		Female thread (DKR)		Female thread (DKOL)		Female thread (DKOL)		Male thread (AGR)	
R+M Nr.	↔	R+M Nr.	↔	R+M Nr.	↔	R+M Nr.	↔	R+M Nr.	↔
471 052 603 5	3.5 m	471 054 603 5	3.5 m	471 072 603 5	3.5 m	471 076 603 5	3.5 m	471 044 603 5	3.5 m
471 052 603 7	3.7 m	471 054 603 7	3.7 m	471 072 603 7	3.7 m	471 076 603 7	3.7 m	471 044 603 7	3.7 m
471 052 604	4.0 m	471 054 604	4.0 m	471 072 604	4.0 m	471 076 604	4.0 m	471 044 604	4.0 m
471 052 604 2	4.2 m	471 054 604 2	4.2 m	471 072 604 2	4.2 m	471 076 604 2	4.2 m	471 044 604 2	4.2 m
471 052 604 5	4.5 m	471 054 604 5	4.5 m	471 072 604 5	4.5 m	471 076 604 5	4.5 m	471 044 604 5	4.5 m
471 052 604 7	4.7 m	471 054 604 7	4.7 m	471 072 604 7	4.7 m	471 076 604 7	4.7 m	471 044 604 7	4.7 m
471 052 605	5.0 m	471 054 605	5.0 m	471 072 605	5.0 m	471 076 605	5.0 m	471 044 605	5.0 m
471 052 605 5	5.5 m	471 054 605 5	5.5 m	471 072 605 5	5.5 m	471 076 605 5	5.5 m	471 044 605 5	5.5 m
471 052 606	6.0 m	471 054 606	6.0 m	471 072 606	6.0 m	471 076 606	6.0 m	471 044 606	6.0 m



Female thread (DKR)		Female thread (DKR)		Female thread (DKOL)		Female thread (DKOL)		Male thread (AGR)	
R+M Nr.	↔	R+M Nr.	↔	R+M Nr.	↔	R+M Nr.	↔	R+M Nr.	↔
471 405 230 35	3.5 m	471 405 430 35	3.5 m	471 407 230 35	3.5 m	471 407 630 35	3.5 m	471 404 430 35	3.5 m
471 405 230 37	3.7 m	471 405 430 37	3.7 m	471 407 230 37	3.7 m	471 407 630 37	3.7 m	471 404 430 37	3.7 m
471 405 230 4	4.0 m	471 405 430 4	4.0 m	471 407 230 4	4.0 m	471 407 630 4	4.0 m	471 404 430 4	4.0 m
471 405 230 42	4.2 m	471 405 430 42	4.2 m	471 407 230 42	4.2 m	471 407 630 42	4.2 m	471 404 430 42	4.2 m
471 405 230 45	4.5 m	471 405 430 45	4.5 m	471 407 230 45	4.5 m	471 407 630 45	4.5 m	471 404 430 45	4.5 m
471 405 230 47	4.7 m	471 405 430 47	4.7 m	471 407 230 47	4.7 m	471 407 630 47	4.7 m	471 404 430 47	4.7 m
471 405 230 5	5.0 m	471 405 430 5	5.0 m	471 407 230 5	5.0 m	471 407 630 5	5.0 m	471 404 430 5	5.0 m
471 405 230 55	5.5 m	471 405 430 55	5.5 m	471 407 230 55	5.5 m	471 407 630 55	5.5 m	471 404 430 55	5.5 m
471 405 230 6	6.0 m	471 405 430 6	6.0 m	471 407 230 6	6.0 m	471 407 630 6	6.0 m	471 404 430 6	6.0 m



Female thread (DKR)		Female thread (DKR)		Female thread (DKOL)		Female thread (DKOL)		Male thread (AGR)	
R+M Nr.	↔	R+M Nr.	↔	R+M Nr.	↔	R+M Nr.	↔	R+M Nr.	↔
471 205 230 35	3.5 m	471 205 430 35	3.5 m	471 207 230 35	3.5 m	471 207 630 35	3.5 m	471 204 430 35	3.5 m
471 205 230 37	3.7 m	471 205 430 37	3.7 m	471 207 230 37	3.7 m	471 207 630 37	3.7 m	471 204 430 37	3.7 m
471 205 230 4	4.0 m	471 205 430 4	4.0 m	471 207 230 4	4.0 m	471 207 630 4	4.0 m	471 204 430 4	4.0 m
471 205 230 42	4.2 m	471 205 430 42	4.2 m	471 207 230 42	4.2 m	471 207 630 42	4.2 m	471 204 430 42	4.2 m
471 205 230 45	4.5 m	471 205 430 45	4.5 m	471 207 230 45	4.5 m	471 207 630 45	4.5 m	471 204 430 45	4.5 m
471 205 230 47	4.7 m	471 205 430 47	4.7 m	471 207 230 47	4.7 m	471 207 630 47	4.7 m	471 204 430 47	4.7 m
471 205 230 5	5.0 m	471 205 430 5	5.0 m	471 207 230 5	5.0 m	471 207 630 5	5.0 m	471 204 430 5	5.0 m
471 205 230 55	5.5 m	471 205 430 55	5.5 m	471 207 230 55	5.5 m	471 207 630 55	5.5 m	471 204 430 55	5.5 m
471 205 230 6	6.0 m	471 205 430 6	6.0 m	471 207 230 6	6.0 m	471 207 630 6	6.0 m	471 204 430 6	6.0 m