

## High pressure hoses per metre

### CARWASH COMFORT



- » Special PES interior very resistant to detergents
- » High-tensile polyester reinforcing
- » Transparent and thermoplastic surface made out of polyurethane
- » Oil-, UV-, ozone-resistant and weatherproof
- » Light weight and flexible in case of low temperatures
- » DN 8 ideally used at foam lances, excellent bending behaviour
- » DN 8: roll at 100 m
- » DN 6: roll at 200 m / 400 m

Field of application: self-service washing bays

R+M Nr.	TYP	DN	Ø	P	BP	°C
300 100 6	blue	6	12.0	200 bar	>800 bar	-40 °C - +60 °C
300 110 6	grey	6	12.0	200 bar	>800 bar	-40 °C - +60 °C
300 120 6	red	6	12.0	200 bar	>800 bar	-40 °C - +60 °C
300 140 6	green	6	12.0	200 bar	>800 bar	-40 °C - +60 °C
300 150 6	yellow	6	12.0	200 bar	>800 bar	-40 °C - +60 °C
300 100 8	blue	8	15.0	200 bar	>800 bar	-40 °C - +60 °C
300 120 8	red	8	15.0	200 bar	>800 bar	-40 °C - +60 °C
300 140 8	green	8	15.0	200 bar	>800 bar	-40 °C - +60 °C

### Plastic



- » Interior polyethylene
- » Polyester inlay free of rotting, high-tensile
- » PVC-surface
- » Limited oil-resistance
- » Roll at 400 m

Field of application: Semi-professional hp cleaning & pipe cleaning

R+M Nr.	TYP	DN	Ø	P	BP	°C
304 01	black	5	9.9	120 bar	≥440 bar	-20 °C - 60 °C



- » Interior polyethylene
- » Polyester inlay free of rotting, high-tensile
- » PVC-surface
- » Limited oil-resistance
- » Roll at 400 m

Field of application: Semi-professional hp cleaning & pipe cleaning

R+M Nr.	TYP	DN	Ø	P	BP	°C
304 10	black	5	10.4	200 bar	≥800 bar	-30 °C - 60 °C



- » Interior polyethylene
- » Polyester inlay free of rotting, high-tensile
- » PVC-surface
- » Limited oil-resistance
- » Roll at 400 m

Field of application: Semi-professional hp cleaning & pipe cleaning

R+M Nr.	TYP	DN	Ø	P	BP	°C
300 01	black	6	11.6	160 bar	≥640 bar	-20 °C - 65 °C

### blupur



- » Interior polyethylene
- » Polyester inlay free of rotting, high-tensile
- » PVC-surface
- » Limited oil-resistance
- » Roll at 400 m. \* Roll at 100 m

Field of application: Semi-professional hp cleaning & pipe cleaning

R+M Nr.	TYP	DN	Ø	P	BP	°C
304 15	blupur	5	10.3	200 bar	≥800 bar	-40 °C - 60 °C
304 18*	blupur	8	13.0	180 bar	≥640 bar	-20 °C - 60 °C

Please note that the hose dimensions given may vary within the DIN.  
Hose sold by the metre may be supplied only in production lengths, otherwise cut costs will arise.