

Jetter Valves



Jetter valves are special valve assemblies which allow to shut off one particular intake valve. The jetter valve cuts off the flow of one of the three pistons of the jetter pump. Due to this the pump starts pulsating which causes significant vibrations at the nozzle and an increased cleaning effect at a reduced flow rate (approx. -1/3 of the full flow rate of the pump). Jetter valves create vibrations to help the hose sliding around tight bends in small lines. Jetter valves should not be combined with pulsation dampers in one jetter unit. Pulsation can be started or stopped by a lever or hand wheel at the jetter valve.

R+M Nr.	TYP
170 402 35	XT, XM
170 401 61	RK
170 402 36	XW

Tip cleaner



High speed steel (HSS) with aluminium shaft.
 ⇄ 42 mm

R+M Nr.	∅
200 049 042	0.5

Drain jet extension

Lance with female thread

1/4" M : 1/4" F BSP.

Drain jet extension for cleaning pipes and shafts of large diameter to prevent reversal in direction of travel.

Max. 400 bar



R+M Nr.	⇄	(M)
070 000 097	100 mm	stainless steel
070 000 098	150 mm	stainless steel
070 000 099	200 mm	stainless steel
070 000 095	250 mm	stainless steel
070 000 101	350 mm	stainless steel

Towing-Eye Kit ST-49



For M5 nozzle bodies

R+M Nr.	∅
200 049 015	0,5



Sting extension



Hardened stainless steel.
 For M5 nozzle bodies

R+M Nr.	(M)
040 075 090	M5 M



Functional principle



Symbols ⇄ outlet (M) inlet ∅ diameter TYP type ⇄ length (M) material