

## Suttner high pressure spray guns

ST-1100



Professional gun.  
Max. 210 bar / 25 l/min / 150 °C

<b>R+M Nr.</b>		
201 100 500	1/4" F	3/8" F



Professional gun.  
Max. 210 bar / 25 l/min / 150 °C

<b>R+M Nr.</b>		
201 100 540	1/4" F	3/8" F swivel



Professional gun.  
Max. 210 bar / 25 l/min / 150 °C

<b>R+M Nr.</b>		
201 100 545	M22 M	M22 M



Professional gun. Weep version.  
Max. 210 bar / 25 l/min / 150 °C

<b>R+M Nr.</b>		
201 100 535	1/4" F	3/8" F



Professional gun. Weep version.  
Max. 210 bar / 25 l/min / 150 °C

<b>R+M Nr.</b>		
201 100 530	1/4" F	3/8" F swivel



Professional gun ST-1100 with coupling KW.  
Max. 210 bar / 25 l/min / 150 °C

<b>R+M Nr.</b>		
201 100 560	coupling KW	3/8" F



Professional gun without valve.  
Max. 210 bar / 25 l/min / 150 °C

<b>R+M Nr.</b>		
201 100 570	1/4" F	3/8" F swivel



Professional gun with extension 340 mm,  
max. 210 bar / 25 l/min / 150 °C.  
Inlet / outlet M22 F. Hose: 6 - 160 (polyester interior), max. 160 bar / 20 °C

<b>R+M Nr.</b>	<b>hose</b>	
201 100 700	6 - 160	8 m



Professional gun with extension 340 mm,  
max. 210 bar / 25 l/min / 150 °C.  
Inlet / outlet M22 F. Hose: Flexy (single wire braid), max. 300 bar / 100 °C

<b>R+M Nr.</b>	<b>hose</b>	
201 100 710	Flexy	8 m



Professional gun with extension 340 mm and M22 F.  
Max. 210 bar / 25 l/min / 150 °C

<b>R+M Nr.</b>		
201 100 522	M22 F	3/8" F



Professional gun with extension 340 mm and M22 F.  
Max. 210 bar / 25 l/min / 150 °C

<b>R+M Nr.</b>		
201 100 523	M22 F	M22 M