

## Pistolets haute-pression, Suttner

## ST-1500



Pistolet professionnel.  
Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 500	1/4" F	3/8" F



Pistolet professionnel.  
Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 560	1/4" F	3/8" F rotatif



Pistolet professionnel.  
Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 550	1/4" F	M22 M





Pistolet professionnel.  
Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 545	M22 M	M22 M



Pistolet professionnel.  
Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 760	M22 F	M22 M



Pistolet professionnel. Version hors-gel avec clapet. Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 580	1/4" F	3/8" F



Pistolet professionnel. Version hors-gel avec clapet. Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 581	1/4" F	3/8" F rotatif



Pistolet professionnel. Version hors-gel pleureur. Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 620	1/4" F	3/8" F



Pistolet professionnel sans clapet (passage libre). Max. 275 bar / 45 l/min / 150 °C

R+M Nr.		
201 500 750	1/4" F	3/8" F

## Raccord tournant, ST-300



1/4" F : 3/8" F. ST-1500

R+M Nr.
200 300 050



Kit de réparation ST-300

R+M Nr.
200 300 100

## Kit de réparation



ST-1100. Entrée rotative

R+M Nr.
200 300 100

## Clapet complet



ST-1100

R+M Nr.
201 100 401

## Clapets complets



ST-1500

R+M Nr.
202 000 044



ST-1500 H/G pleureur

R+M Nr.
202 000 045



ST-1500 H/G avec clapet

R+M Nr.
202 000 101

Symboles  sortie  entrée