

## Gun extensions



1/4" M. Lance with insulation ST-28 Cool & Compact.  
Max. 400 bar / 150 °C

R+M Nr.	☺	ISO	↔	M
200 028 303	1/4" M	300 mm	330 mm	zinc-plated steel



1/4" M. Lance with insulation ST-29 Cool & Compact. Max. 400 bar / 150 °C

R+M Nr.	☺	ISO	↔	M
200 029 303	1/4" M	300 mm	330 mm	stainless steel



1/4" M. Lance with insulation ST-9.1 and M22 F.  
Max. 400 bar / 150 °C

R+M Nr.	☺	↔	M
200 009 730	M22 F	350 mm	stainless steel
200 009 731	M22 F	350 mm	zinc-plated steel



1/4" M. Lance with insulation ST-9.1 and coupling KW.  
Max. 400 bar / 150 °C

R+M Nr.	☺	↔	M
200 009 750	coupling KW	260 mm	stainless steel



1/4" M. Lance with insulation and M22 F.  
Max. 400 bar / 150 °C

R+M Nr.	☺	↔	M
202 300 400	M22 F	340 mm	zinc-plated steel



1/4" M. Lance with insulation ST-9.9 and M22 F.  
Max. 400 bar / 150 °C

R+M Nr.	☺	↔	M
200 009 945	M22 F	370 mm	zinc-plated steel



1/4" M. Lance with insulation ST-9.9 and M22 F.  
Max. 400 bar / 150 °C

R+M Nr.	☺	↔	M
200 009 940	M22 F	370 mm	zinc-plated steel



1/4" M. Lance with moulded handle.  
Max. 400 bar / 150 °C

R+M Nr.	☺	ISO	↔	M
070 004 340	1/4" M	400 mm	440 mm	stainless steel



1/4" M. Lance with moulded handle.  
Max. 400 bar / 150 °C

R+M Nr.	☺	ISO	↔	M
070 000 330	1/4" M	300 mm	330 mm	zinc-plated steel
070 000 240	1/4" M	400 mm	440 mm	zinc-plated steel



1/4" M. Lance with moulded handle.  
Max. 400 bar / 150 °C

R+M Nr.	☺	ISO	↔	M
070 003 229	1/4" M	300 mm	330 mm	stainless steel

Symbols ☺ outlet ISO insulation ↔ length M material