

## Manchons de pistolet



1/4" M. Manchon ST-28 Cool & Compact.  
Max. 400 bar / 150 °C

R+M Nr.	⊖	ISO	⊕	M
200 028 303	1/4" M	300 mm	330 mm	acier zingué



1/4" M. Manchon avec manchon ST-29 Cool & Compact.  
Max. 400 bar / 150 °C

R+M Nr.	⊖	ISO	⊕	M
200 029 303	1/4" M	300 mm	330 mm	inox



1/4" M. Manchons avec coquilles ST-9.1 et raccord manuel M22.  
Max. 400 bar / 150 °C

R+M Nr.	⊖	ISO	⊕	M
200 009 730	M22 F		350 mm	inox
200 009 731	M22 F		350 mm	acier zingué



1/4" M. Manchon avec coquilles ST-9.1 et coupleur KW.  
Max. 400 bar / 150 °C

R+M Nr.	⊖	ISO	⊕	M
200 009 750	coupleur KW		260 mm	inox



1/4" M. Manchon surmoulé et raccord manuel M22.  
Max. 400 bar / 150 °C

R+M Nr.	⊖	ISO	⊕	M
202 300 400	M22 F		340 mm	acier zingué



1/4" M. Manchon avec isolation ST-9.9-19 330 mm et raccord manuel M22.  
Max. 400 bar / 150 °C

R+M Nr.	⊖	ISO	⊕	M
200 009 945	M22 F		370 mm	acier zingué



1/4" M. Manchon avec isolation ST-9.9-22 330 mm et raccord manuel M22.  
Max. 400 bar / 150 °C

R+M Nr.	⊖	ISO	⊕	M
200 009 940	M22 F		370 mm	acier zingué



1/4" M. Manchon surmoulé.  
Max. 400 bar / 150 °C

R+M Nr.	⊖	ISO	⊕	M
070 004 340	1/4" M	400 mm	440 mm	inox



1/4" M. Manchons surmoulés.  
Max. 400 bar / 150 °C

R+M Nr.	⊖	ISO	⊕	M
070 000 330	1/4" M	300 mm	330 mm	acier zingué
070 000 240	1/4" M	400 mm	440 mm	acier zingué



1/4" M. Manchon surmoulé.  
Max. 400 bar / 150 °C

R+M Nr.	⊖	ISO	⊕	M
070 003 229	1/4" M	300 mm	330 mm	inox