

Lances

ST-29 Cool & Compact



Lance with insulation ST-29 Cool & Compact. Comfortable grip and ergonomic shape. Heat-proof insulation. Max. 400 bar / 150 °C

R+M Nr.	⊙	ISO	↔	M	R+M Nr.
200 029 305	1/4" M	300 mm	500 mm	stainless steel	
200 029 306	1/4" M	300 mm	600 mm	stainless steel	
200 029 307	1/4" M	300 mm	700 mm	stainless steel	
200 029 309	1/4" M	300 mm	900 mm	stainless steel	
200 029 410	1/4" M	400 mm	1,000 mm	stainless steel	
200 029 312 *	1/4" M	300 mm	1,200 mm	stainless steel	
200 029 412	1/4" M	400 mm	1,200 mm	stainless steel	

ST-007




Lance with moulded handle. Max. 400 bar / 150 °C

R+M Nr.	⊙	ISO	↔	M	R+M Nr.
070 005 010	1/4" M	300 mm	500 mm	stainless steel	
070 010 010	1/4" M	400 mm	1,000 mm	stainless steel	



1/4" M. Lance with moulded handle and nozzle protector ST-10 without high pressure nozzle. Max. 400 bar / 150 °C

R+M Nr.	⊖	ISO	↔	M	R+M Nr.
512 149 3	1/4" F NPT	300 mm	500 mm	stainless steel	
512 449 3	1/4" F NPT	400 mm	1,000 mm	stainless steel	



1/4" M. Lance with moulded handle and nozzle protector ST-10 without high pressure nozzle. Max. 400 bar / 150 °C

R+M Nr.	⊖	ISO	↔	M	R+M Nr.
512 449 31	1/4" F NPT	400 mm	1,000 mm	stainless steel	

U-lances



1/4" M. Lance with moulded handle. Max. 250 bar / 150 °C

R+M Nr.	⊖	ISO	↔	M	R+M Nr.
070 009 011	2 x 1/4" M	300 mm	900 mm	stainless steel	

Symbols ⊖ outlet ↔ length M material ISO insulation ⊙ thread