

Twin lances

Lance with valve ST-54 aside



1/4" M. Lance with moulded handle, valve ST-54 aside and nozzle protector ST-10 with low pressure nozzle & thread 1/4" F. Max. 310 bar / 150 °C

R+M Nr.		ISO		M
200 054 600	1/4" F NPT	300 mm	980 mm	stainless steel

R+M Nr.		ISO		M
517 60	1/4" F NPT	300 mm	980 mm	zinc-plated steel



M22 F. Lance with moulded handle, valve ST-54 aside and nozzle protector ST-10 with low pressure nozzle & thread 1/4" F. Max. 310 bar / 150 °C

R+M Nr.		ISO		M
517 601 9	1/4" F NPT	300 mm	980 mm	stainless steel

R+M Nr.		ISO		M
517 601	1/4" F NPT	300 mm	980 mm	zinc-plated steel



Plug KW. Lance with moulded handle, valve ST-54 aside and nozzle protector ST-10 with low pressure nozzle & thread 1/4" F. Max. 310 bar / 150 °C

R+M Nr.		ISO		M
200 054 630	1/4" F NPT	300 mm	980 mm	stainless steel

R+M Nr.		ISO		M
516 605	1/4" F NPT	300 mm	980 mm	zinc-plated steel

Spare parts are on pages 270 and 271.

Symbols inlet outlet length material insulation