

ST-85 Push & Pull lances



M22 F swivel. ST-85 Push & Pull lance with nozzle protector ST-10 without high pressure nozzle. Max. 210 bar / 150 °C

R+M Nr.	⊖	↔	⊕	M
200 085 713	1/4" F NPT	850 mm	M22 F swivel	zinc-plated steel
200 085 703	1/4" F NPT	1,000 mm	M22 F swivel	zinc-plated steel
200 085 753	1/4" F NPT	1,500 mm	M22 F swivel	zinc-plated steel



K

M22 F. ST-85 Push & Pull lance with nozzle protector without tip. Max. 210 bar / 150 °C

R+M Nr.	⊖	↔	⊕	M
200 085 620 nozzle protector	850 mm	M22 F	stainless steel	
200 085 660 nozzle protector	1,500 mm	M22 F	stainless steel	
R+M Nr.	⊖	↔	⊕	M
200 085 720 nozzle protector	850 mm	M22 F	zinc-plated steel	
200 085 760 nozzle protector	1,500 mm	M22 F	zinc-plated steel	



K

M22 F swivel. ST-85 Push & Pull lance with nozzle protector without tip. Max. 210 bar / 150 °C

R+M Nr.	⊖	↔	⊕	M
200 085 640 nozzle protector	850 mm	M22 F swivel	stainless steel	
200 085 930 nozzle protector	1,000 mm	M22 F swivel	stainless steel	
200 085 680 nozzle protector	1,500 mm	M22 F swivel	stainless steel	
R+M Nr.	⊖	↔	⊕	M
200 085 740 nozzle protector	850 mm	M22 F swivel	zinc-plated steel	
200 085 920 nozzle protector	1,000 mm	M22 F swivel	zinc-plated steel	
200 085 780 nozzle protector	1,500 mm	M22 F swivel	zinc-plated steel	



suitable for standard spray guns

K

M22 F swivel. ST-85 Push & Pull lance with ergonomic swivel screw coupling suitable for standard spray guns. Max. 210 bar / 150 °C

R+M Nr.	⊖	↔	⊕	M
200 085 645 nozzle protector	850 mm	M22 F swivel	stainless steel	
200 085 935 nozzle protector	1,000 mm	M22 F swivel	stainless steel	
200 085 685 nozzle protector	1,500 mm	M22 F swivel	stainless steel	
200 085 687 nozzle protector	2,000 mm	M22 F swivel	stainless steel	
R+M Nr.	⊖	↔	⊕	M
200 085 745 nozzle protector	850 mm	M22 F swivel	zinc-plated steel	
200 085 925 nozzle protector	1,000 mm	M22 F swivel	zinc-plated steel	
200 085 785 nozzle protector	1,500 mm	M22 F swivel	zinc-plated steel	



suitable for servopress spray guns

K

M22 F swivel. ST-85 Push & Pull lance with ergonomic swivel screw coupling suitable for standard spray guns. Max. 210 bar / 150 °C

R+M Nr.	⊖	↔	⊕	M
200 085 646 nozzle protector	850 mm	M22 F swivel	stainless steel	
200 085 936 nozzle protector	1,000 mm	M22 F swivel	stainless steel	
200 085 686 nozzle protector	1,500 mm	M22 F swivel	stainless steel	
200 085 688 nozzle protector	2,000 mm	M22 F swivel	stainless steel	
R+M Nr.	⊖	↔	⊕	M
200 085 746 nozzle protector	850 mm	M22 F swivel	zinc-plated steel	
200 085 926 nozzle protector	1,000 mm	M22 F swivel	zinc-plated steel	
200 085 786 nozzle protector	1,500 mm	M22 F swivel	zinc-plated steel	