

Suttner rotating nozzles with ceramic insert

ST-357.1



1/4" F. Spray angle 20°.
100 - 250 bar. Max. 100 °C

R+M Nr.	D
200 357 530	03
200 357 535	035
200 357 540	04
200 357 545	045
200 357 550	05
200 357 555	055
200 357 560	06
200 357 565	065
200 357 570	07
200 357 580	08
200 357 690	09
200 357 510	100



Kit ST-357.1

R+M Nr.	D
200 357 130	
200 357 135	
200 357 140	
200 357 145	
200 357 150	
200 357 155	
200 357 160	
200 357 165	
200 357 170	
200 357 280	
200 357 290	
200 357 110	



M18 F. Spray angle 20°.
100 - 250 bar. Max. 100 °C

R+M Nr.	D
200 357 330	03
200 357 335	035
200 357 340	04
200 357 345	045
200 357 350	05
200 357 355	055
200 357 360	06
200 357 365	065
200 357 370	07
200 357 380	08
200 357 390	09
200 357 310	100



Kit ST-357.1

R+M Nr.	D
200 357 130	
200 357 135	
200 357 140	
200 357 145	
200 357 150	
200 357 155	
200 357 160	
200 357 165	
200 357 170	
200 357 280	
200 357 290	
200 357 110	



1/8" M. Spray angle 20°.
100 - 250 bar. Max. 100 °C

R+M Nr.	D
200 357 430	03
200 357 435	035
200 357 440	04
200 357 445	045
200 357 450	05
200 357 455	055
200 357 460	06
200 357 465	065
200 357 470	07
200 357 480	08
200 357 490	09
200 357 410	100



Kit ST-357.1

R+M Nr.	D
200 357 130	
200 357 135	
200 357 140	
200 357 145	
200 357 150	
200 357 155	
200 357 160	
200 357 165	
200 357 170	
200 357 280	
200 357 290	
200 357 110	

ST-458.1



1/4" F. Spray angle 20°.
200 - 400 bar. Max. 100 °C

R+M Nr.	D
200 458 630	03
200 458 635	035
200 458 640	04
200 458 645	045
200 458 650	05
200 458 655	055
200 458 660	06
200 458 665	065
200 458 670	07
200 458 680	08
200 458 690	09
200 458 610	100



Kit ST-458.1

R+M Nr.	D
200 458 230	
200 458 235	
200 458 240	
200 458 245	
200 458 250	
200 458 255	
200 458 260	
200 458 265	
200 458 270	
200 458 280	
200 458 290	
200 458 210	



M18 F. Spray angle 20°.
200 - 400 bar. Max. 100 °C

R+M Nr.	D
200 458 331	03
200 458 335	035
200 458 340	04
200 458 345	045
200 458 350	05
200 458 355	055
200 458 360	06
200 458 365	065
200 458 370	07
200 458 380	08
200 458 390	09
200 458 310	100



Kit ST-458.1

R+M Nr.	D
200 458 230	
200 458 235	
200 458 240	
200 458 245	
200 458 250	
200 458 255	
200 458 260	
200 458 265	
200 458 270	
200 458 280	
200 458 290	
200 458 210	



1/8" M. Spray angle 20°.
200 - 400 bar. Max. 100 °C

R+M Nr.	D
200 458 430	03
200 458 435	035
200 458 440	04
200 458 445	045
200 458 450	05
200 458 455	055
200 458 460	06
200 458 465	065
200 458 470	07
200 458 480	08
200 458 490	09
200 458 410	100



Kit ST-458.1

R+M Nr.	D
200 458 230	
200 458 235	
200 458 240	
200 458 245	
200 458 250	
200 458 255	
200 458 260	
200 458 265	
200 458 270	
200 458 280	
200 458 290	
200 458 210	