

Suttner Rotordüsen mit Keramikeinsatz

ST-456



1/4" IG. Spritzwinkel 20°.
200 - 350 bar. Max. 100 °C

R+M Nr.	D
200 456 530	03
200 456 535	035
200 456 540	04
200 456 545	045
200 456 550	05
200 456 555	055
200 456 560	06
200 456 565	065
200 456 570	07
200 456 580	08



Kit ST-456

R+M Nr.	D
200 456 130	
200 456 135	
200 456 140	
200 456 145	
200 456 150	
200 456 155	
200 456 160	
200 456 165	
200 456 170	
200 456 180	



M1/8 IG. Spritzwinkel 20°.
200 - 350 bar. Max. 100 °C

R+M Nr.	D
200 456 630	03
200 456 635	035
200 456 640	04
200 456 645	045
200 456 650	05
200 456 655	055
200 456 660	06
200 456 665	065
200 456 670	07
200 456 680	08
200 456 690 *	09



Kit ST-456

R+M Nr.	D
200 456 130	
200 456 135	
200 456 140	
200 456 145	
200 456 150	
200 456 155	
200 456 160	
200 456 165	
200 456 170	
200 456 180	
200 456 190	

ST-458.1



1/4" IG. Spritzwinkel 20°.
120 - 250 bar. Max. 100 °C

R+M Nr.	D
200 458 811	110
200 458 812	120
200 458 813	130
200 458 815	150
200 458 818	180
200 458 820	200
200 458 825	250
200 458 830	300



Kit ST-458.1

R+M Nr.	D
200 458 311	
200 458 312	
200 458 313	
200 458 315	
200 458 318	
200 458 320	
200 458 325	
200 458 330	



1/2" IG. Spritzwinkel 20°.
120 - 250 bar. Max. 100 °C

R+M Nr.	D
200 458 712	120
200 458 715	150
200 458 720	200
200 458 730	300



Kit ST-458.1

R+M Nr.	D
200 458 312	
200 458 315	
200 458 320	
200 458 330	



1/2" IG. Spritzwinkel 20°.
120 - 250 bar. Max. 100 °C

R+M Nr.	D
200 458 745	045
200 458 755	055
200 458 770	07
200 458 791	09



Kit ST-458.1

R+M Nr.	D
200 458 245	
200 458 255	
200 458 270	
200 458 290	

Suttner Rotordüsen mit Hartmetalleinsatz

ST-559



1/4" IG. 300-600 bar. Max. 90 °C

R+M Nr.	D
200 559 520	02
200 559 530	03
200 559 540	04
200 559 550	05
200 559 555	055
200 559 560	06



M20x1 IG. 300-600 bar. Max. 90 °C

R+M Nr.	D
200 559 320	02
200 559 330	03
200 559 340	04



Kit ST-559

R+M Nr.	D
200 559 120	
200 559 130	
200 559 140	
200 559 150	
200 559 155	
200 559 160	

* Restposten