

new

Quick connect nozzle set by Suttner

- » Consisting of:
colored plastic holder inclusive:
1 x Low pressure nozzle. Brass,
1 x Flushing nozzle. Stainless steel,
1 x Chiseling nozzle. Stainless steel,
1 x Blasting nozzle. Stainless steel
- » High strength plastic. Highly impact resistant
- » Stainless steel nozzles: long lifetime and excellently thermal and chemical stability, resistant to mineral acids and alkaline solutions.
- » Connection ST-245 coupling, \odot 1/4" F, R+M Nr. 200 245 500
- » Suitable for applications requiring a frequent and quick change of the spraying angle
- » Max. 350 bar



D	R+M Nr.	\odot
030	125 852 030	ST-245
035	125 852 035	ST-245
040	125 852 040	ST-245
045	125 852 045	ST-245
050	125 852 050	ST-245
055	125 852 055	ST-245
060	125 852 060	ST-245
070	125 852 070	ST-245



Colour coding of Suttner nozzle set holder according to nozzle size

030 yellow	035 purple	040 brown	045 green
050 black	055 blue	060 red	070 orange

- Low pressure nozzle.** Brass. Designed for prespraying detergents on all kinds of surfaces. Low pressure rinsing.
- Flushing nozzle.** Stainless steel. Best suited for flushing dirt, mud and grime.
- Chiseling nozzle.** Stainless steel. The spray should be directed at a 45° angle to the surface and used like a scraper to remove paint, grease and dirt.
- Blasting nozzle.** Stainless steel. Delivers a very concentrated stream of water. Care should be used to avoid gouging wood or damaging fragile surfaces.

Coupling-system ST-245

Nipple ST-245

\odot 1/4" M. Stainless steel. Max. 350 bar	\odot 1/4" M. Stainless steel. Max. 350 bar	\odot 1/4" M. Stainless steel. Max. 350 bar. For wear cone
R+M Nr. 040 005 447 27.5	R+M Nr. 040 005 446 33.5	R+M Nr. 040 005 445 3 42.0

ST-245 Coupling / wear cone ST-245

R+M Nr. 200 245 500 1 1/4" F	R+M Nr. 200 245 510 1 3/8" M	
Stainless steel. For 040 005 445	POM. Red. For 040 005 445	POM. Black. For 040 005 445
R+M Nr. 040 005 431 2	R+M Nr. 020 005 432 2	R+M Nr. 020 005 431 2

4

Suitable for all 1/4" F nozzles for sewer cleaning.

1 2 3 4