

turbodevil - our new turbodevil floor cleaner series

turbodevil – BASIC

- » Especially designed for professional cleaning applications
- » **Max. 60 °C. 1,000 r.p.m. at 3 - 60 °C**
- » Completely stainless design
- » Heat-resistant all around protection ensures a safe handling by protection against splashes and stones
- » The precision rotor arm is counterbalanced, precisely equilibrated and welded by robots
- » Low vibration and reliable running
- » Suitable for applications up to about 150 annual operation hours are guaranteed

Surface cleaner TD 300 BASIC

Surface cleaner TD 410 BASIC



Surface cleaner with a newly developed swivel with pivoting inlet for high revolutions per minute. The bending of the swivel is variably adjustable thus making an easy cleaning of floors and walls possible. 3 industrial castors (60 mm). 2 nozzles 1/4" M are required. Max. 1,800 l/h / 60 °C. Max. 275 bar

R+M Nr.	∅	⊕	R+M Nr.	∅	⊕
521 030 300	300 mm	1/4" F	521 042 300	410 mm	1/4" F

Surface cleaner TD 410 BASIC



Surface cleaner with foldable handle bar for space saving and reasonable transport. Swivel with triple bearing system. 3 industrial castors (60 mm). 2 nozzles 1/4" M are required. Max. 1,800 l/h / 60 °C. Max. 275 bar

R+M Nr.	∅	⊕	P
521 042 350	410 mm	1/4" F	max. 275 bar

Symbols ⊕ inlet P pressure ∅ diameter




Newly developed:
Swivel for high revolutions with pivoting inlet



3 or 4 industrial castors (60 mm):
Easy and flexible steering



Precision rotor:
Welded by robots



Surface cleaner TD 520 BASIC



Swivel:
With triple bearing system

ST-2600
LTF

We recommend using the gun ST-2600 with patented LTF technology.

Surface cleaner with foldable handle bar for space saving and reasonable transport. Swivel with triple bearing system. 4 industrial castors (60 mm). 2 nozzles 1/4" M are required. Max. 2,400 l/h / 60 °C

R+M Nr.	∅	⊕	P	incl.
521 052 300	520 mm	1/4" F	max. 275 bar	-
521 052 301	520 mm	3/8" F	max. 275 bar	ST-2600
521 052 304	520 mm	3/8" F	max. 275 bar	ST-2600 swivel
521 052 302	520 mm	M22 F	max. 275 bar	-
521 052 303	520 mm	Plug KW	max. 275 bar	-