

Cartridge filter



Plastic cleanable. Reinforced version.
Max. 40 °C

R+M Nr.	★	fi	microns	⌈
734 293 00	■ ■	5"	60	125
734 293 02	■ ■ ■ ■	9.3/4"	60	250
734 293 03	■ ■ ■ ■	9.3/4"	120	250



Plastic cleanable.
Max. 40 °C

R+M Nr.	★	fi	microns	⌈
734 55	■	5"	60	128
734 54	■	5"	150	128
734 75	■ ■ ■ ■	9.3/4"	60	250
734 74	■ ■ ■ ■	9.3/4"	150	250



Cotton.
Max. 40 °C

R+M Nr.	★	fi	microns	⌈
734 57	■	5"	5	128
734 56	■	5"	20	128
734 77	■ ■ ■ ■	9.3/4"	5	250
734 76	■ ■ ■ ■	9.3/4"	20	250



Iron remove filter

R+M Nr.	★	fi	⊖	⌈
734 709 060	■ ■ ■ ■	9.3/4"	0.85	250



Water softener. Polyphosphate

R+M Nr.	★	fi	⊖	⌈
734 58	■ ■	5"	1.8	125

**The filters
734 709 060 and 734 58
are not suitable for the
water supply of pumps.**



Polypropylene. Max. 40 °C

R+M Nr.	★	fi	microns	⌈
734 720 006	■	20"	5	510
734 720 050	■	20"	50	510



Stainless steel. Max. 120 °C

R+M Nr.	★	fi	microns	⌈
734 709 050	■ ■ ■ ■	9.3/4"	50	250

The higher the number of microns the more coarsely meshed are the meshes: 500 microns = coarse . 50 microns = fine

Symbols ★ marking fi filter ⊙ thread ⌈ height TYP type ⊖ flow