

Mosmatic floor cleaner

Mosmatic surface cleaner FL-AHY 520



Completely stainless steel. Surface cleaner with an additional frame for highest stability. A height adjustable housing including a device for extraction. Foldable handle bar for space saving and reasonable transport. 2 nozzles are required. Suitable for 50 mm suction hose. 4 industrial castors (100 mm). Max. 2,400 l/h / 120 °C

R+M Nr.	∅	G	P
108 809 71	520 mm	1/4" F	max. 500 bar

Mosmatic roof cleaner DR-520



precision rotor arm

adjustable height

hose connection

Completely stainless steel. Roof cleaner with an additional frame for highest stability. Adjustable in width of up to 90 mm and in height of up to 33 mm. Including a safety loop for the safety rope with clippers. The use of the ST-550 foot valve is recommended. 4 industrial castors (125 mm). Max. 2,400 l/h / 120 °C

R+M Nr.	∅	G	P
108 809 72	520 mm	3/8" F	max. 350 bar
108 809 73	520 mm	3/8" F	max. 500 bar

Mosmatic surface cleaner FL-SAR 300



Surface cleaner AQUA with recovery. Complete with integrated suction system, spray gun and nozzles. Recovery Port: 40 mm. Designed for 150 bar / 15 l / min. The black anodized aluminum suction device collects the dirty water via a Venturi and double housing system. It can then be led away via a commercially available suction hose. The use of a vacuum system is no longer needed. Max. 275 bar / 120 °C.

R+M Nr.	∅	G	P
108 782 43	300 mm	3/8" F	max. 275 bar

The accident prevention regulations of the Employer's Liability Insurance Association regarding "the use of high pressure cleaner" (BGV D15) & "tasks with liquid jets" (BGV D26) in addition to DIN EN 60335-2-79 and DIN EN 1829-1 prescribe that manually guided spray units (like roof cleaners) shall be provided with a manually-actuated control for release of the cleaning solution.

Mosmatic cleaning head TRS

- » If water pressure is produced the rotor arms start turning by themselves. The arm rotates by means of the repulsive force of the water jet and does not need any additional drive.
- » Completely made out of stainless steel, with swivel DYT.
- » Nozzles are excluded. 4 EG nozzle tips are required.



Inlet 3/8" F.
Max. 170 bar / 120 °C

R+M Nr.
108 819 19